

# Häufige Probleme beim Debuggen von TACACS+, PAP und CHAP

## Inhalt

[Einführung](#)  
[Voraussetzungen](#)  
[Anforderungen](#)  
[Verwendete Komponenten](#)  
[Konventionen](#)  
[Allgemeine PC-Einstellungen](#)  
[Windows 95](#)  
[Windows NT](#)  
[Windows 98](#)  
[Windows 2000](#)  
[Konfigurationen und Debugbeispiele](#)  
[Befehle für andere Cisco IOS-Versionen](#)  
[Beispieldebugging - TACACS+ und PAP](#)  
[Befehle für andere Cisco IOS-Versionen](#)  
[Beispieldebugging - TACACS+ und CHAP](#)  
[Debug-Befehle](#)  
[Zugehörige Informationen](#)

## [Einführung](#)

**Hinweis:** Die Informationen in diesem Dokument basieren auf den Cisco IOS® Software-Versionen 11.2 und höher.

Dieses Dokument untersucht häufige Debugprobleme für TACACS+, wenn Password Authentication Protocol (PAP) oder Challenge Handshake Authentication Protocol (CHAP) verwendet werden. Gängige PC-Einstellungen für Microsoft Windows 95, Windows NT, Windows 98 und Windows 2000 sowie Beispiele für Konfigurationen und Beispiele für gute und schlechte Debugging-Optionen werden bereitgestellt.

## [Voraussetzungen](#)

### [Anforderungen](#)

Für dieses Dokument bestehen keine speziellen Anforderungen.

### [Verwendete Komponenten](#)

Dieses Dokument ist nicht auf bestimmte Software- und Hardwareversionen beschränkt.

Die Informationen in diesem Dokument wurden von den Geräten in einer bestimmten Laborumgebung erstellt. Alle in diesem Dokument verwendeten Geräte haben mit einer leeren (Standard-)Konfiguration begonnen. Wenn Ihr Netzwerk in Betrieb ist, stellen Sie sicher, dass Sie die potenziellen Auswirkungen eines Befehls verstehen.

## Konventionen

Weitere Informationen zu Dokumentkonventionen finden Sie unter [Cisco Technical Tips Conventions](#) (Technische Tipps zu Konventionen von Cisco).

## Allgemeine PC-Einstellungen

### Windows 95

Gehen Sie wie folgt vor:

1. Wählen Sie im Fenster Dialup Networking (DFÜ-Netzwerk) den Namen der Verbindung und dann **File > Properties (Datei > Eigenschaften)**.
2. Überprüfen Sie auf der Registerkarte Servertyp, ob das Kontrollkästchen **Verschlüsseltes Kennwort** unter Typ des DFÜ-Servers aktiviert ist. Wenn dieses Kontrollkästchen aktiviert ist, akzeptiert der PC nur die CHAP-Authentifizierung. Wenn dieses Kontrollkästchen nicht aktiviert ist, akzeptiert der PC die PAP- oder CHAP-Authentifizierung.

### Windows NT

Gehen Sie wie folgt vor:

1. Wählen Sie im Fenster DFÜ-Netzwerk den Namen der Verbindung aus, und wählen Sie dann **Datei > Eigenschaften**.
2. Überprüfen Sie die Einstellungen auf der Registerkarte Sicherheit: Wenn das Kontrollkästchen **Authentifizierung einschließlich Klartext akzeptieren** aktiviert ist, akzeptiert der PC PAP oder CHAP. Wenn das Kontrollkästchen **Nur verschlüsselte Authentifizierung akzeptieren** aktiviert ist, akzeptiert der PC nur die CHAP-Authentifizierung.

### Windows 98

Gehen Sie wie folgt vor:

1. Wählen Sie im Fenster DFÜ-Netzwerk den Namen der Verbindung aus, und wählen Sie dann **Eigenschaften aus**.
2. Überprüfen Sie auf der Registerkarte Servertypen die Einstellungen im Bereich Erweiterte Optionen: Wenn das Kontrollkästchen **Verschlüsseltes Kennwort** anfordern nicht aktiviert ist, akzeptiert der PC die PAP- oder CHAP-Authentifizierung. Wenn das Kontrollkästchen **Verschlüsseltes Kennwort** anfordern aktiviert ist, akzeptiert der PC nur die CHAP-Authentifizierung.

## Windows 2000

Gehen Sie wie folgt vor:

1. Wählen Sie unter Netzwerk- und DFÜ-Verbindungen den Namen der Verbindung aus, und wählen Sie dann **Eigenschaften aus**.
2. Wählen Sie auf der Registerkarte Sicherheit im Bereich **Erweitert > Einstellungen > Diese Protokolle zulassen** folgende Protokolle aus: Wenn das Kontrollkästchen **Uncrypted Password (PAP)** aktiviert ist, akzeptiert der PC PAP. Wenn das Kontrollkästchen **Challenge Handshake Authentication Protocol (CHAP)** aktiviert ist, akzeptiert der PC CHAP gemäß RFC 1994. Wenn das Kontrollkästchen **Microsoft CHAP (MS-CHAP)** aktiviert ist, akzeptiert der PC MS-CHAP Version 1 und akzeptiert kein CHAP gemäß RFC 1994.

## Konfigurationen und Debugbeispiele

### **Konfiguration - TACACS+ und PAP**

```
Current configuration:

!
version 11.2
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
service udp-small-servers
service tcp-small-servers
!
hostname rtpkrb
!
aaa new-model
!
!---- The following four lines of the !--- configuration
are specific to !--- Cisco IOS 11.2 and later, until
11.3.3.T. !--- See below this configuration !--- for
commands for other Cisco IOS releases. ! aaa
authentication login default tacacs+ local
aaa authentication ppp default if-needed tacacs+ local
aaa authorization exec tacacs+ if-authenticated
aaa authorization network tacacs+ if-authenticated
enable secret 5 $1$pkX.$JdAySRE1SbdbDe7bj0wyt0
enable password ww
!
username john password 0 doe
username cse password 0 csecse
ip host rtpkrb 10.31.1.5
ip domain-name RTP.CISCO.COM
ip name-server 171.68.118.103
!
interface Loopback0
ip address 1.1.1.1 255.255.255.0
!
interface Ethernet0
ip address 10.31.1.5 255.255.0.0
no mop enabled
!
interface Serial0
no ip address
```

```

no ip mroute-cache
shutdown
!
interface Serial1
no ip address
shutdown
!
interface Async1
ip unnumbered Ethernet0
encapsulation ppp
async mode dedicated
peer default ip address pool async
no cdp enable
ppp authentication pap
!
ip local pool async 15.15.15.15
ip classless
ip route 0.0.0.0 0.0.0.0 10.31.1.1
!
tacacs-server host 171.68.118.101
tacacs-server key cisco
snmp-server community public RW
snmp-server host 171.68.118.100 traps public
!
line con 0
line 1
session-timeout 20
exec-timeout 20 0
password ww
autoselect during-login
autoselect ppp
modem InOut
transport input all
stopbits 1
speed 38400
flowcontrol hardware
line 2
modem InOut
speed 38400
flowcontrol hardware
line 3 16
line aux 0
line vty 0 4
password ww
!
end

```

## Befehle für andere Cisco IOS-Versionen

**Hinweis:** Um diese Befehle zu verwenden, entfernen Sie fett formatierte Befehle aus der Konfiguration, und fügen Sie diese Befehle gemäß der Cisco IOS-Version ein.

### Cisco IOS 11.3.3.T bis 12.0.5.T

```

aaa authen login default tacacs+ local
aaa authen ppp default if-needed tacacs+ local
aaa authorization exec default tacacs+ if-authenticated
aaa authorization network default tacacs+ if-authenticated

```

### Cisco IOS 12.0.5.T und höher

```
aaa authen login default group tacacs+ local
aaa authen ppp default if-needed group tacacs+ local
aaa authorization exec default group tacacs+ if-authenticated
aaa authorization network default group tacacs+ if-authenticated
```

## Beispieldebugging - TACACS+ und PAP

**Hinweis:** In der Debugausgabe wird der fett formatierte Text auf Probleme beim Debuggen hinweisen. Einfacher Text weist auf eine gute Fehlersuche hin.

```
rtpkrb#show debug
General OS:
TACACS access control debugging is on
AAA Authentication debugging is on
AAA Authorization debugging is on
PPP:
PPP authentication debugging is on
PPP protocol negotiation debugging is on
rtpkrb#
3d22h: %LINK-3-UPDOWN: Interface Async1, changed state to up
3d22h: As1 PPP: Treating connection as a dedicated line
3d22h: As1 PPP: Phase is ESTABLISHING, Active Open
3d22h: As1 LCP: O CONFREQ [Closed] id 14 len 24
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto PAP (0x0304C023)
3d22h: As1 LCP: MagicNumber 0xF45FB7A7 (0x0506F45FB7A7)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
!--- PC insists on doing CHAP !--- ("accept encrypted authentication only"), !--- but router is set up for PAP. As1 LCP: I CONFNAK [REQsent] id 27 len 12
As1 LCP: AuthProto 0xC123 (0x0308C12301000001)
As1 PPP: Closing connection because remote won't authenticate

3d22h: As1 LCP: Interface transitioned, discarding packet
3d22h: As1 LCP: I CONFACK [REQsent] id 14 len 24
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto PAP (0x0304C023)
3d22h: As1 LCP: MagicNumber 0xF45FB7A7 (0x0506F45FB7A7)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: TIMEout: Time 0x14417CC4 State ACKrcvd
3d22h: As1 LCP: O CONFREQ [ACKrcvd] id 15 len 24
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto PAP (0x0304C023)
3d22h: As1 LCP: MagicNumber 0xF45FB7A7 (0x0506F45FB7A7)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: I CONFACK [REQsent] id 15 len 24
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto PAP (0x0304C023)
3d22h: As1 LCP: MagicNumber 0xF45FB7A7 (0x0506F45FB7A7)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: I CONFREQ [ACKrcvd] id 0 len 20
3d22h: As1 LCP: ACCM 0x00000000 (0x020600000000)
3d22h: As1 LCP: MagicNumber 0x000030A3 (0x0506000030A3)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: O CONFACK [ACKrcvd] id 0 len 20
3d22h: As1 LCP: ACCM 0x00000000 (0x020600000000)
3d22h: As1 LCP: MagicNumber 0x000030A3 (0x0506000030A3)
```

```

3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: State is Open
3d22h: As1 PPP: Phase is AUTHENTICATING, by this end
3d22h: As1 PAP: I AUTH-REQ id 4 len 20 from "papuser"
3d22h: As1 PAP: Authenticating peer papuser
3d22h: AAA/AUTHEN: create_user (0x16D4C0) user='papuser'
ruser='' port='Async1' rem_addr='async' authen_type=PAP
service=PPP priv=1
3d22h: AAA/AUTHEN/START (1190231344): port='Async1' list=''
action=LOGIN service=PPP
3d22h: AAA/AUTHEN/START (1190231344): using "default" list
3d22h: AAA/AUTHEN (1190231344): status = UNKNOWN
3d22h: AAA/AUTHEN/START (1190231344): Method=TACACS+
3d22h: TAC+: send AUTHEN/START packet ver=193 id=1190231344
3d22h: TAC+: Using default tacacs server list.
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5

    --- The TAC+ server is down, producing an error. !--- Since the user is not in the local
database, !--- the failover to local fails. TAC+: TCP/IP open to 171.68.118.101/49 failed --
Connection refused by remote host
AAA/AUTHEN (866823886): status = ERROR
AAA/AUTHEN/START (866823886): Method=LOCAL
AAA/AUTHEN (866823886): status = FAIL

3d22h: TAC+: Opened TCP/IP handle 0x16C1F8 to 171.68.118.101/49
3d22h: TAC+: 171.68.118.101 (1190231344) AUTHEN/START/LOGIN/PAP queued
3d22h: TAC+: (1190231344) AUTHEN/START/LOGIN/PAP processed

    --- The key in the router does not match that of the server. TAC+: received bad AUTHEN packet:
length = 68, expected 67857
TAC+: Invalid AUTHEN/START packet (check keys)
AAA/AUTHEN (1771887965): status = ERROR

3d22h: TAC+: ver=192 id=1190231344 received AUTHEN status = GETPASS
3d22h: TAC+: Closing TCP/IP 0x16C1F8 connection to 171.68.118.101/49
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16EF4C to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: AAA/AUTHEN: create_user (0x16C5EC) user='papuser' ruser=''
port='Async1' rem_addr='async' authen_type=PAP service=PPP priv=1
3d22h: TAC+: rev0 inbound pap login for id=1190231344 using id=3112896669
3d22h: TAC+: 171.68.118.101 (3112896669) AUTHEN/START/LOGIN/PAP queued
3d22h: TAC+: (3112896669) AUTHEN/START/LOGIN/PAP processed
3d22h: TAC+: ver=192 id=3112896669 received AUTHEN status = GETPASS
3d22h: TAC+: send AUTHEN/CONT packet
3d22h: TAC+: 171.68.118.101 (3112896669) AUTHEN/CONT queued
3d22h: TAC+: (3112896669) AUTHEN/CONT processed

    --- The NT client sends the "DOMAIN\user" !--- and the TAC+ server expects "user". TAC+:
ver=192 id=260507389 received AUTHEN status = FAIL
TAC+: rev0 inbound pap completed for 1139034411 status=FAIL
AAA/AUTHEN: free_user (0x16CDD4) user='CISCO\papuser' ruser=''
port='Async1' rem_addr='async' authen_type=PAP service=PPP priv=1

    --- The TAC+ server refuses the user !--- because the user is set up for PAP. !--- The user
enters a bad password, !--- or both the username and password are bad. TAC+: ver=192
id=691012958 received AUTHEN status = FAIL
TAC+: rev0 inbound pap completed for 3917384959 status=FAIL
AAA/AUTHEN: free_user (0x15AD58) user='idochap' ruser=''
port='Async1' rem_addr='async' authen_type=PAP service=PPP priv=1

3d22h: TAC+: ver=192 id=3112896669 received AUTHEN status = PASS
3d22h: TAC+: rev0 inbound pap completed for 1190231344 status=PASS

```

```

3d22h: AAA/AUTHEN: free_user (0x16C5EC) user='papuser' ruser=''
port='Async1' rem_addr='async' authen_type=PAP service=PPP priv=1
3d22h: TAC+: Closing TCP/IP 0x16EF4C connection to 171.68.118.101/49
3d22h: AAA/AUTHEN (1190231344): status = PASS
3d22h: AAA/AUTHOR/LCP As1: Authorize LCP
3d22h: AAA/AUTHOR/LCP: Async1: (1061976769): user='papuser'
3d22h: AAA/AUTHOR/LCP: Async1: (1061976769): send AV service=ppp
3d22h: AAA/AUTHOR/LCP: Async1: (1061976769): send AV protocol=lcp
3d22h: AAA/AUTHOR/LCP: Async1: (1061976769): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (1061976769): user=papuser
3d22h: AAA/AUTHOR/TAC+: (1061976769): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (1061976769): send AV protocol=lcp
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16C9E0 to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (1061976769) AUTHOR/START queued
3d22h: TAC+: (1061976769) AUTHOR/START processed

---- The user passes authentication !--- (the username/password is good) !--- but fails
authorization !--- (the profile is not set up to authorize PPP). TAC+: (1793875816): received
author response status = FAIL
TAC+: Closing TCP/IP 0x17054C connection to 171.68.118.101/49
AAA/AUTHOR (1793875816): Post authorization status = FAIL
AAA/AUTHOR/LCP As1: Denied

3d22h: TAC+: (1061976769): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x16C9E0 connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (1061976769): Post authorization status = PASS_ADD
3d22h: As1 PAP: O AUTH-ACK id 4 len 5
3d22h: As1 PPP: Phase is UP
3d22h: AAA/AUTHOR/FSM As1: (0): Can we start IPCP?
3d22h: AAA/AUTHOR/FSM: Async1: (3602788894): user='papuser'
3d22h: AAA/AUTHOR/FSM: Async1: (3602788894): send AV service=ppp
3d22h: AAA/AUTHOR/FSM: Async1: (3602788894): send AV protocol=ip
3d22h: AAA/AUTHOR/FSM: Async1: (3602788894): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (3602788894): user=papuser
3d22h: AAA/AUTHOR/TAC+: (3602788894): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (3602788894): send AV protocol=ip
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: %LINEPROTO-5-UPDOWN: Line protocol on Interface Async1,
changed state to up
3d22h: TAC+: Opened TCP/IP handle 0x17054C to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (3602788894) AUTHOR/START queued
3d22h: As1 IPCP: I CONFREQ [Closed] id 1 len 34
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)
3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: TAC+: (3602788894) AUTHOR/START processed
3d22h: TAC+: (3602788894): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x17054C connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (3602788894): Post authorization status = PASS_ADD
3d22h: AAA/AUTHOR/FSM As1: We can start IPCP
3d22h: As1 IPCP: O CONFREQ [Closed] id 10 len 10
3d22h: As1 IPCP: Address 10.31.1.5 (0x03060A1F0105)
3d22h: As1 IPCP: I CONFACK [REQsent] id 10 len 10
3d22h: As1 IPCP: Address 10.31.1.5 (0x03060A1F0105)
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 1 len 34
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)

```

```

3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 0.0.0.0,
we want 0.0.0.0
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 0.0.0.0,
we want 0.0.0.0
3d22h: As1 IPCP: Using pool 'async'
3d22h: As1 IPCP: Pool returned 15.15.15.15
3d22h: As1 IPCP: O CONFREJ [ACKrcvd] id 1 len 22
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)
3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 2 len 16
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 0.0.0.0,
we want 15.15.15.15
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 0.0.0.0,
we want 15.15.15.15
3d22h: As1 IPCP: O CONFNAK [ACKrcvd] id 2 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 3 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 15.15.15.15,
we want 15.15.15.15
3d22h: AAA/AUTHOR/IPCP: Async1: (3654974050): user='papuser'
3d22h: AAA/AUTHOR/IPCP: Async1: (3654974050): send AV service=ppp
3d22h: AAA/AUTHOR/IPCP: Async1: (3654974050): send AV protocol=ip
3d22h: AAA/AUTHOR/IPCP: Async1: (3654974050): send AV addr*15.15.15.15
3d22h: AAA/AUTHOR/IPCP: Async1: (3654974050): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (3654974050): user=papuser
3d22h: AAA/AUTHOR/TAC+: (3654974050): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (3654974050): send AV protocol=ip
3d22h: AAA/AUTHOR/TAC+: (3654974050): send AV addr*15.15.15.15
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16EF4C to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (3654974050) AUTHOR/START queued
3d22h: TAC+: (3654974050) AUTHOR/START processed
3d22h: TAC+: (3654974050): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x16EF4C connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (3654974050): Post authorization status = PASS_ADD
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Processing AV addr*15.15.15.15
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 15.15.15.15,
we want 15.15.15.15
3d22h: As1 IPCP: O CONFACK [ACKrcvd] id 3 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: As1 IPCP: State is Open
3d22h: As1 IPCP: Install route to 15.15.15.15
rtpkrb#

```

## Konfiguration - TACACS+ und CHAP

```
Current configuration:
!
version 11.2
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
service udp-small-servers
service tcp-small-servers
!
hostname rtpkrb
!
aaa new-model
!
!---- The following four lines of the configuration !---
are specific to Cisco IOS 11.2 and later, until
11.3.3.T. !--- See below this configuration !--- for
commands for other Cisco IOS releases. ! aaa
authentication login default tacacs+ local
aaa authentication ppp default if-needed tacacs+ local
aaa authorization exec tacacs+ if-authenticated
aaa authorization network tacacs+ if-authenticated
enable secret 5 $1$pkX.$JdAySRE1SbdbDe7bj0wyt0
enable password ww
!
username john password 0 doe
username cse password 0 csecse
ip host rtpkrb 10.31.1.5
ip name-server 171.68.118.103
!
interface Loopback0
ip address 1.1.1.1 255.255.255.0
!
interface Ethernet0
ip address 10.31.1.5 255.255.0.0
no mop enabled
!
interface Serial0
no ip address
no ip mroute-cache
shutdown
!
interface Serial1
no ip address
shutdown
!
interface Async1
ip unnumbered Ethernet0
encapsulation ppp
async mode dedicated
peer default ip address pool async
no cdp enable
ppp authentication chap
!
ip local pool async 15.15.15.15
ip classless
ip route 0.0.0.0 0.0.0.0 10.31.1.1
!
tacacs-server host 171.68.118.101
tacacs-server key cisco
snmp-server community public RW
snmp-server host 171.68.118.100 traps public
!
line con 0
line 1
```

```
session-timeout 20
exec-timeout 20 0
password ww
autoselect during-login
autoselect ppp
modem InOut
transport input all
stopbits 1
speed 38400
flowcontrol hardware
line 2
modem InOut
speed 38400
flowcontrol hardware
line 3 16
line aux 0
line vty 0 4
password ww
!
end
```

## Befehle für andere Cisco IOS-Versionen

**Hinweis:** Hinweis: Um diese Befehle zu verwenden, entfernen Sie fett formatierte Befehle aus der Konfiguration und fügen diese Befehle gemäß der Cisco IOS-Version ein.

### Cisco IOS 11.3.3.T bis 12.0.5.T

```
aaa authen login default tacacs+ local
aaa authen ppp default if-needed tacacs+ local
aaa authorization exec default tacacs+ if-authenticated
aaa authorization network default tacacs+ if-authenticated
```

### Cisco IOS 12.0.5.T und höher

```
aaa authen login default group tacacs+ local
aaa authen ppp default if-needed group tacacs+ local
aaa authorization exec default group tacacs+ if-authenticated
aaa authorization network default group tacacs+ if-authenticated
```

## Beispieldebugging - TACACS+ und CHAP

**Hinweis:** In der Debugausgabe wird der fett formatierte Text auf Probleme beim Debuggen hinweisen. Einfacher Text weist auf eine gute Fehlersuche hin.

```
General OS:
TACACS access control debugging is on
AAA Authentication debugging is on
AAA Authorization debugging is on
PPP:
PPP authentication debugging is on
PPP protocol negotiation debugging is on
rtpkrb#
3d22h: As1 LCP: I CONFREQ [Closed] id 0 len 20
3d22h: As1 LCP: ACCM 0x00000000 (0x020600000000)
3d22h: As1 LCP: MagicNumber 0x000042C5 (0x0506000042C5)
3d22h: As1 LCP: PFC (0x0702)
```

```

3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: Lower layer not up, discarding packet
3d22h: %LINK-3-UPDOWN: Interface Async1, changed state to up
3d22h: As1 PPP: Treating connection as a dedicated line
3d22h: As1 PPP: Phase is ESTABLISHING, Active Open
3d22h: As1 LCP: O CONFREQ [Closed] id 12 len 25
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto CHAP (0x0305C22305)
3d22h: As1 LCP: MagicNumber 0xF45D776F (0x0506F45D776F)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: I CONFACK [REQsent] id 12 len 25
3d22h: As1 LCP: ACCM 0x000A0000 (0x0206000A0000)
3d22h: As1 LCP: AuthProto CHAP (0x0305C22305)
3d22h: As1 LCP: MagicNumber 0xF45D776F (0x0506F45D776F)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: I CONFREQ [ACKrcvd] id 0 len 20
3d22h: As1 LCP: ACCM 0x00000000 (0x020600000000)
3d22h: As1 LCP: MagicNumber 0x000042C5 (0x0506000042C5)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: O CONFACK [ACKrcvd] id 0 len 20
3d22h: As1 LCP: ACCM 0x00000000 (0x020600000000)
3d22h: As1 LCP: MagicNumber 0x000042C5 (0x0506000042C5)
3d22h: As1 LCP: PFC (0x0702)
3d22h: As1 LCP: ACFC (0x0802)
3d22h: As1 LCP: State is Open
3d22h: As1 PPP: Phase is AUTHENTICATING, by this end
3d22h: As1 CHAP: O CHALLENGE id 3 len 27 from "rtpkrb"
3d22h: As1 CHAP: I RESPONSE id 3 len 29 from "chapuser"
3d22h: AAA/AUTHEN: create_user (0x15B394) user='chapuser'
ruser='' port='Async1' rem_addr='async' authen_type=CHAP
service=PPP priv=1
3d22h: AAA/AUTHEN/START (2183639772): port='Async1' list=''
action=LOGIN service=PPP
3d22h: AAA/AUTHEN/START (2183639772): using "default" list
3d22h: AAA/AUTHEN (2183639772): status = UNKNOWN
3d22h: AAA/AUTHEN/START (2183639772): Method=TACACS+
3d22h: TAC+: send AUTHEN/START packet ver=193 id=2183639772
3d22h: TAC+: Using default tacacs server list.
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5

    --- The TAC+ server is down, producing an error. !--- Since the user is not in the local
    database, !--- the failover to local fails. TAC+: TCP/IP open to 171.68.118.101/49 failed --
Connection refused by remote host
AAA/AUTHEN (2546660185): status = ERROR
AAA/AUTHEN/START (2546660185): Method=LOCAL
AAA/AUTHEN (2546660185): status = FAIL
As1 CHAP: Unable to validate Response. Username chapuser: Authentication failure

3d22h: TAC+: Opened TCP/IP handle 0x17054C to 171.68.118.101/49
3d22h: TAC+: 171.68.118.101 (2183639772) AUTHEN/START/LOGIN/CHAP queued
3d22h: TAC+: (2183639772) AUTHEN/START/LOGIN/CHAP processed

    --- The key in the router does not match that of the server. TAC+: received bad AUTHEN packet:
length = 68, expected 67857
TAC+: Invalid AUTHEN/START packet (check keys)
AAA/AUTHEN (1771887965): status = ERROR

3d22h: TAC+: ver=192 id=2183639772 received AUTHEN status = GETPASS
3d22h: TAC+: Closing TCP/IP 0x17054C connection to 171.68.118.101/49
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16EF4C to 171.68.118.101/49

```

```

3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: AAA/AUTHEN: create_user (0x170940) user='chapuser' ruser=''
port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1
3d22h: TAC+: rev0 inbound chap for id=2183639772 using id=166703029
3d22h: TAC+: 171.68.118.101 (166703029) AUTHEN/START/SENDPASS/CHAP queued
3d22h: TAC+: (166703029) AUTHEN/START/SENDPASS/CHAP processed

!--- The NT client sends the "DOMAIN\user" !--- and the TAC+ server expects "user". TAC+:
ver=192 id=3373385106 received AUTHEN status = FAIL
TAC+: rev0 inbound chap FAIL for id=2082151566
AAA/AUTHEN: free_user (0x170940) user='CISCO\chapuser' ruser=''
port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1

!--- The TAC+ server refuses the user !--- because the user is set up for PAP. !--- The user
enters a bad password, !--- or both the username and password are bad. TAC+: ver=192
id=1989464562 received AUTHEN status = PASS
TAC+: rev0 inbound chap SENDPASS status=PASS for id=3657266965
TAC+: rev0 inbound chap MD5 compare FAILED
AAA/AUTHEN: free_user (0x170940) user='chapuser' ruser=''
port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1
TAC+: Closing TCP/IP 0x16EF4C connection to 171.68.118.101/49
AAA/AUTHEN (2082151566): status = FAIL
As1 CHAP: Unable to validate Response. Username papuser: Authentication failure

3d22h: TAC+: ver=192 id=166703029 received AUTHEN status = PASS
3d22h: TAC+: rev0 inbound chap SENDPASS status=PASS for id=2183639772
3d22h: TAC+: rev0 inbound chap MD5 compare OK
3d22h: AAA/AUTHEN: free_user (0x170940) user='chapuser' ruser=''
port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1
3d22h: TAC+: Closing TCP/IP 0x16EF4C connection to 171.68.118.101/49
3d22h: AAA/AUTHEN (2183639772): status = PASS
3d22h: AAA/AUTHOR/LCP As1: Authorize LCP
3d22h: AAA/AUTHOR/LCP: Async1: (683360936): user='chapuser'
3d22h: AAA/AUTHOR/LCP: Async1: (683360936): send AV service=ppp
3d22h: AAA/AUTHOR/LCP: Async1: (683360936): send AV protocol=lcp
3d22h: AAA/AUTHOR/LCP: Async1: (683360936): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (683360936): user=chapuser
3d22h: AAA/AUTHOR/TAC+: (683360936): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (683360936): send AV protocol=lcp
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16C1F8 to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (683360936) AUTHOR/START queued
3d22h: TAC+: (683360936) AUTHOR/START processed

!--- The user passes authentication !--- (the username/password is good) !--- but fails
authorization !--- (the profile is not set up to authorize PPP). TAC+: (3803447096): received
author response status = FAIL
TAC+: Closing TCP/IP 0x16C2A4 connection to 171.68.118.101/49
AAA/AUTHOR (3803447096): Post authorization status = FAIL
AAA/AUTHOR/LCP As1: Denied
AAA/AUTHEN: free_user (0x15B2E8) user='noauth' ruser='' port='Async1'
rem_addr='async' authen_type=CHAP service=PPP priv=1
As1 CHAP: O FAILURE id 9 len 24 msg is "Authorization failed"

3d22h: TAC+: (683360936): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x16C1F8 connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (683360936): Post authorization status = PASS_ADD
3d22h: As1 CHAP: O SUCCESS id 3 len 4
3d22h: As1 PPP: Phase is UP
3d22h: AAA/AUTHOR/FSM As1: (0): Can we start IPCP?
3d22h: AAA/AUTHOR/FSM: Async1: (977509495): user='chapuser'
3d22h: AAA/AUTHOR/FSM: Async1: (977509495): send AV service=ppp
3d22h: AAA/AUTHOR/FSM: Async1: (977509495): send AV protocol=ip

```

```
3d22h: AAA/AUTHOR/FSM: Async1: (977509495): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (977509495): user=chapuser
3d22h: AAA/AUTHOR/TAC+: (977509495): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (977509495): send AV protocol=ip
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16EF4C to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (977509495) AUTHOR/START queued
3d22h: As1 IPCP: I CONFREQ [Closed] id 1 len 34
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)
3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: TAC+: (977509495) AUTHOR/START processed
3d22h: TAC+: (977509495): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x16EF4C connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (977509495): Post authorization status = PASS_ADD
3d22h: AAA/AUTHOR/FSM As1: We can start IPCP
3d22h: As1 IPCP: O CONFREQ [Closed] id 8 len 10
3d22h: As1 IPCP: Address 10.31.1.5 (0x03060A1F0105)
3d22h: As1 IPCP: I CONFACK [REQsent] id 8 len 10
3d22h: As1 IPCP: Address 10.31.1.5 (0x03060A1F0105)
3d22h: %LINEPROTO-5-UPDOWN: Line protocol on Interface Async1,
changed state to up
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 1 len 34
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)
3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 0.0.0.0,
we want 0.0.0.0
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 0.0.0.0,
we want 0.0.0.0
3d22h: As1 IPCP: Using pool 'async'
3d22h: As1 IPCP: Pool returned 15.15.15.15
3d22h: As1 IPCP: O CONFREJ [ACKrcvd] id 1 len 22
3d22h: As1 IPCP: PrimaryWINS 0.0.0.0 (0x820600000000)
3d22h: As1 IPCP: SecondaryDNS 0.0.0.0 (0x830600000000)
3d22h: As1 IPCP: SecondaryWINS 0.0.0.0 (0x840600000000)
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 2 len 16
3d22h: As1 IPCP: Address 0.0.0.0 (0x030600000000)
3d22h: As1 IPCP: PrimaryDNS 0.0.0.0 (0x810600000000)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 0.0.0.0,
we want 15.15.15.15
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 0.0.0.0,
we want 15.15.15.15
3d22h: As1 IPCP: O CONFNAK [ACKrcvd] id 2 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: As1 IPCP: I CONFREQ [ACKrcvd] id 3 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: AAA/AUTHOR/IPCP As1: Start. Her address 15.15.15.15,
we want 15.15.15.15
3d22h: AAA/AUTHOR/IPCP: Async1: (3918374858): user='chapuser'
3d22h: AAA/AUTHOR/IPCP: Async1: (3918374858): send AV service=ppp
```

```
3d22h: AAA/AUTHOR/IPCP: Async1: (3918374858): send AV protocol=ip
3d22h: AAA/AUTHOR/IPCP: Async1: (3918374858): send AV addr*15.15.15.15
3d22h: AAA/AUTHOR/IPCP: Async1: (3918374858): Method=TACACS+
3d22h: AAA/AUTHOR/TAC+: (3918374858): user=chapuser
3d22h: AAA/AUTHOR/TAC+: (3918374858): send AV service=ppp
3d22h: AAA/AUTHOR/TAC+: (3918374858): send AV protocol=ip
3d22h: AAA/AUTHOR/TAC+: (3918374858): send AV addr*15.15.15.15
3d22h: TAC+: Opening TCP/IP to 171.68.118.101/49 timeout=5
3d22h: TAC+: Opened TCP/IP handle 0x16C9E0 to 171.68.118.101/49
3d22h: TAC+: Opened 171.68.118.101 index=1
3d22h: TAC+: 171.68.118.101 (3918374858) AUTHOR/START queued
3d22h: TAC+: (3918374858) AUTHOR/START processed
3d22h: TAC+: (3918374858): received author response status = PASS_ADD
3d22h: TAC+: Closing TCP/IP 0x16C9E0 connection to 171.68.118.101/49
3d22h: AAA/AUTHOR (3918374858): Post authorization status = PASS_ADD
3d22h: AAA/AUTHOR/IPCP As1: Processing AV service=ppp
3d22h: AAA/AUTHOR/IPCP As1: Processing AV protocol=ip
3d22h: AAA/AUTHOR/IPCP As1: Processing AV addr*15.15.15.15
3d22h: AAA/AUTHOR/IPCP As1: Authorization succeeded
3d22h: AAA/AUTHOR/IPCP As1: Done. Her address 15.15.15.15,
we want 15.15.15
3d22h: As1 IPCP: 0 CONFACK [ACKrcvd] id 3 len 16
3d22h: As1 IPCP: Address 15.15.15.15 (0x03060F0F0F0F)
3d22h: As1 IPCP: PrimaryDNS 171.68.118.103 (0x8106AB447667)
3d22h: As1 IPCP: State is Open
3d22h: As1 IPCP: Install route to 15.15.15.15
rtpkrb#
```

## Debug-Befehle

Diese Debugbefehle wurden verwendet, um die Beispieldebugausgabe in diesem Dokument zu erstellen.

**Hinweis:** Bevor Sie Debugbefehle ausgeben, informieren Sie sich unter [Wichtige Informationen über Debug-Befehle](#).

- **debug aaa authentication:** Zeigt Informationen zur AAA-Authentifizierung an.
- **debug aaa authorization:** Zeigt Informationen über die AAA-Autorisierung an.
- **debug tacacs+:** Zeigt detaillierte Debuginformationen zu TACACS+ an.
- **debug ppp negotiation:** Zeigt PPP-Pakete an, die während des PPP-Starts übertragen werden und über die PPP-Optionen ausgehandelt werden.

## Zugehörige Informationen

- [TACACS+ in der IOS-Dokumentation](#)
- [Support-Seite für TACACS+](#)
- [Technischer Support und Dokumentation - Cisco Systems](#)