

# Fehlerbehebung in einem Szenario in Zusammenhang mit Bulkstats-Schemas und empfohlenen Problemumgehungen in StarOS

## Inhalt

[Einleitung](#)

[Voraussetzungen](#)

[Anforderungen](#)

[Verwendete Komponenten](#)

[Hintergrundinformationen](#)

[Problem](#)

[Testszenarien](#)

[Lösung](#)

## Einleitung

Dieses Dokument beschreibt ein Szenario für das Hinzufügen und Löschen von bulkstat-Schemas in StarOS zusammen mit Problemen und empfohlenen Problemumgehungen für diese Probleme.

## Voraussetzungen

### Anforderungen

Cisco empfiehlt, dass Sie über Kenntnisse in folgenden Bereichen verfügen:

- Linux
- StarOS

Cisco empfiehlt, dass Sie über folgende Berechtigungen verfügen müssen:

- ausgeblendeter Modus, um die **Debug-Shell** auszuführen, um auf die Befehlszeile der Linux-Shell zuzugreifen
- Secure File Transfer Protocol (SFTP)-Zugriff auf den StarOS-Knoten

### Verwendete Komponenten

Die Informationen in diesem Dokument basieren auf der StarOS-Version-21.16.6.77063.

Die Informationen in diesem Dokument beziehen sich auf Geräte in einer speziell eingerichteten Testumgebung. Alle Geräte, die in diesem Dokument benutzt wurden, begannen mit einer gelöschten (Nichterfüllungs) Konfiguration. Wenn Ihr Netzwerk in Betrieb ist, stellen Sie sicher, dass Sie die potenziellen Auswirkungen eines Befehls verstehen.

# Hintergrundinformationen

1. So konfigurieren Sie eine Konfigurationsdatei zum Speichern der Konfigurationen für bulkstats.
2. Das Format des Befehls ist:

```
configure
    [no] bulkstats config [ schema | supplement ] <url>
end
```

Wo:

- Mit dem optionalen **Schema**-Schlüsselwort können Sie nur das Schema mit der bereitgestellten Datei ersetzen und die Serverkonfiguration beibehalten.
- Mit dem optionalen **Supplement**-Schlüsselwort können Sie die aktuelle bulkstats-Konfiguration durch den Inhalt der bereitgestellten Konfigurationsdatei ergänzen. Diese Schlüsselwörter funktionieren nur mit vorhandenen Dateien.
- URL gibt den Speicherort der bulkstats-Konfigurationsdatei an.

## Problem

Es ist nicht möglich, über die CLI-Eingabeaufforderung neue Schemas hinzuzufügen bzw. das aktuelle Schema (wenn gelöscht) erneut hinzuzufügen.

## Testszenarios

1. Dieses Problem wurde durch die Verwendung des CLI **bulkstat-Konfigurationsschemas** **<URL>** verursacht.
2. Es ist ein erwartetes Ergebnis pro Design, wenn ein optionales Schlüsselwortschema verwendet wird.
3. Das gleiche Szenario wurde im Labor getestet. Dies sind die Ergebnisse:  
Szenario A. Ursprünglich wurde **bulkstat config <url>** cli konfiguriert.

```
[local]MME# show configuration bulkstats
config
    bulkstats collection
    bulkstats historical collection
    bulkstats config /hd-raid/file1
    bulkstats mode
    file 1
    header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%
```

footer format EndOfFile

card schema cardSch1 format

PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numproc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,

card schema cardSch2 format

PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,

card schema cardSch3 format

PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%,

port schema portSch1 format

PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%,%txbytes%,%ucast\_inpackets%,%ucast\_outpackets%,%mcast\_inpackets%,%mcast\_outpackets%,%bcast\_inpackets%,%bcast\_outpackets%,%rxpackets%,%txpackets%,%rxdiscbytes%,%rxdiscpackets%,%txdiscbytes%,%txdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,

port schema portSch2 format

PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-reassembled%,%frag-tokernel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-15peak-tx-util%,

apn-expansion schema apn1 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion schema apn2 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

apn-expansion schema apn3 format PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,

#exit

#exit

end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

|                             |                             |
|-----------------------------|-----------------------------|
| Server State:               | Enabled                     |
| File Limit:                 | 7500 KB                     |
| Sample Interval:            | 15 minutes (0D 0H 15M)      |
| Transfer Interval:          | 480 minutes (0D 8H 0M)      |
| Receiver Mode:              | Secondary-on-failure        |
| Historical Data Collection: | Enabled (15 samples stored) |

Bulk Statistics Server Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last collection time required: 0 second(s)  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last transfer time required: 0 second(s)  
No successful data transfers

No attempted data transfers

File 2 not configured

File 3 not configured

File 4 not configured

----- Schemas for File 1-----

| Type          | Name     | Active-Only | Format  |
|---------------|----------|-------------|---|
| card          | cardSch1 | No          | PPM,card,cardSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpubusy%,%cpuidle%,%numproc%,%memused%,%memtotal%,%numcpu%,%cpu0-cpubusy%,%cpu0-cpuidle%,%cpu0-numproc%,%cpu0-memused%,%cpu0-memtotal%,%cpu0-name%,%cpu0-cpuused-user%,%cpu0-cpuused-sys%,%cpu0-cpuused-io%,%cpu0-cpuused-irq%,%cpu0-cpuused-idle%,%cpu1-cpubusy%,%cpu1-cpuidle%,%cpu1-numproc%,   |
| card          | cardSch2 | No          | PPM,card,cardSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu1-memused%,%cpu1-memtotal%,%cpu1-name%,%cpu1-cpuused-user%,%cpu1-cpuused-sys%,%cpu1-cpuused-io%,%cpu1-cpuused-irq%,%cpu1-cpuused-idle%,%cpu2-cpubusy%,%cpu2-cpuidle%,%cpu2-numproc%,%cpu2-memused%,%cpu2-memtotal%,%cpu2-name%,%cpu2-cpuused-user%,%cpu2-cpuused-sys%,%cpu2-cpuused-io%,%cpu2-cpuused-irq%,%cpu2-cpuused-idle%,%cpu3-cpubusy%,%cpu3-cpuidle%,   |
| card          | cardSch3 | No          | PPM,card,cardSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%cpu3-numproc%,%cpu3-memused%,%cpu3-memtotal%,%cpu3-name%,%cpu3-cpuused-user%,%cpu3-cpuused-sys%,%cpu3-cpuused-io%,%cpu3-cpuused-irq%,%cpu3-cpuused-idle%,%15avg-cpubusy%,%15peak-cpubusy%,%5avg-cpubusy%,%5peak-cpubusy%,%1avg-cpubusy%,%15avg-memused%,%15peak-memused%,%5avg-memused%,%5peak-memused%,%1avg-memused%,%cpu0-15avg-cpubusy%,%cpu0-15peak-cpubusy%, |
| port          | portSch1 | No          | PPM,port,portSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%maxrate%,%rxbytes%,%txbytes%,%ucast_inpackets%,%ucast_outpackets%,%mcast_inpackets%,%mcast_outpackets%,%bcast_inpackets%,%bcast_outpackets%,%rxpackets%,%txpackets%,%rxdisbytes%,%rxdiscpackets%,%txdisbytes%,%txdiscpackets%,%rxerrorbytes%,%rxerrorpackets%,%txerrorbytes%,%txerrorpackets%,  |
| port          | portSch2 | No          | PPM,port,portSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%card%,%port%,%frag-rcvd%,%pkt-reassembled%,%frag-tokenel%,%util-rx-curr%,%util-tx-curr%,%util-rx-5min%,%util-tx-5min%,%util-rx-15min%,%util-tx-15min%,%port-5peak-rx-util%,%port-5peak-tx-util%,%port-15peak-rx-util%,%port-15peak-tx-util%,  |
| apn-expansion | apn1     | No          | PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,  |
| apn-expansion | apn2     | No          | PPM,apn-expansion,%epochtime%,%localdate%,%localtime%,  |

```
apn-expansion apn3                No                PPM, apn-
expansion,%epochtime%,%localdate%,%localtime%,

mon-di-net   mdn1                No                PPM,%epochtime%,%localdate%,%localtime%,
```

```
[local]MME#
```

Szenario B. Um das optionale Schlüsselwortschema **hinzuzufügen**, müssen Sie zunächst die **bulkstat-CLI ohne bulkstats config** entfernen. Wenn Sie **keine bulkstats-Konfiguration** ausführen, werden alle aktuellen Schemas im Knoten gelöscht.

```
[local]MME#
```

```
[local]MME# configure
```

```
[local]MME(config)# bulkstats collection
```

```
[local]MME(config)# no bulkstats config
```

```
<cr>                - newline
```

```
[local]MME(config)# no bulkstats config
```

```
[local]MME(config)# end
```

```
[local]MME# show configuration bulkstats
```

```
config
```

```
bulkstats collection
```

```
bulkstats historical collection
```

```
bulkstats mode
```

```
file 1
```

```
header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-
%localtime%,%localtz%,%localtzooffset%,%localdate3%-%localtime3%,%swbuild%
```

```
footer format EndOfFile
```

```
#exit
```

```
#exit
```

```
end
```

```
[local]MME# show bulkstats schemas
```

```
Bulk Statistics Server Configuration:
```

```
Server State:                Enabled
```

```
File Limit:                   7500 KB
```

```
Sample Interval:             15 minutes (0D 0H 15M)
```

```
Transfer Interval:           480 minutes (0D 8H 0M)
```

```
Receiver Mode:               Secondary-on-failure
```

```
Historical Data Collection:   Enabled (15 samples stored)
```

Bulk Statistics Server Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last collection time required: 0 second(s)  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last transfer time required: 0 second(s)

No successful data transfers

No attempted data transfers

File 2 not configured

File 3 not configured

File 4 not configured

[local]MME#

[local]MME#

Szenario C, dann die CLI **bulkstat config schema** <url> wird konfiguriert. Alle in der Konfigurationsdatei vorhandenen Konfigurationen und Schemas werden dem Knoten hinzugefügt.

[local]MME# configure

[local]MME(config)# bulkstats collection

[local]MME(config)# bulkstats config schema /hd-raid/file2

Info: config

Info: bulkstats mode

Info: file 2

Info: header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

Info: footer format EndOfFile

Info: diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

Info: diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%sta-ans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

Info: diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

Info: schema systemSch1 format

PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-

ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

Info: schema systemSch10 format

PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

Info: schema systemSch100 format

PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

Info: sgs schema sgsSch1 format

PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

Info: sgs schema sgsSch2 format

PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

Info: sgs schema sgsSch3 format

PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

Info: exit

[local]MME(config)# end

[local]MME#

[local]MME# show configuration bulkstats

config

bulkstats collection

bulkstats historical collection

bulkstats config schema /hd-raid/file2

bulkstats mode

file 1

header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-

%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

footer format EndOfFile

#exit

file 2

header format Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

footer format EndOfFile

schema systemSch1 format

PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaabuffused%,%sess-curaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

schema systemSch10 format

PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

schema systemSch100 format

PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth schema diameter-authSch1 format PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth schema diameter-authSch2 format PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth schema diameter-authSch3 format PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs schema sgsSch1 format

PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

sgs schema sgsSch2 format

```
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,
```

```
sgs schema sgsSch3 format
```

```
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,
```

```
#exit
```

```
#exit
```

```
end
```

```
[local]MME#
```

Szenario D. Danach ist es nicht mehr möglich, neue Schemas hinzuzufügen. Wenn Sie versuchen, ein aktuelles Schema zu entfernen und es erneut hinzuzufügen, wird das Schema gelöscht, Sie können es jedoch nicht erneut hinzufügen. Das aktuelle Schema war jedoch weiterhin in der Konfigurationsdatei vorhanden (Konfigurationsdatei im URL vorhanden).

```
[local]MME# configure
```

```
[local]MME(config)# bulkstats mode
```

mode - Enters bulk statistics configuration mode, where you can define what statistics to collect

```
[local]MME(config)# bulkstats mode
```

```
[local]MME(config-bulkstats)# file 1
```

```
[local]MME(config-bulkstats-file-1)# mon-di-net schema mdn1 format PPM,%epochti
me%,%localdate%,%localtime%,
```

```
[local]MME(config-bulkstats-file-1)# exit
```

```
[local]MME(config-bulkstats)# file 2
```

```
[local]MME(config-bulkstats-file-2)# mon-di-net schema mdn2 format PPM,%epochti
me%,
```

```
[local]MME(config-bulkstats-file-2)# end
```

```
[local]MME# show bulkstats schemas
```

Bulk Statistics Server Configuration:

```
Server State:           Enabled
File Limit:             7500 KB
Sample Interval:       15 minutes (0D 0H 15M)
```

Transfer Interval: 480 minutes (0D 8H 0M)  
Receiver Mode: Secondary-on-failure  
Historical Data Collection: Enabled (15 samples stored)

Bulk Statistics Server Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last collection time required: 0 second(s)  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0

Total records discarded: 0  
Total bytes discarded: 0  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

| Type | Name | Active-Only Format |
|------|------|--------------------|
|------|------|--------------------|

-----

system systemSch1 No  
PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconn%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaaabuffused%,%sess-curaaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,

system systemSch10 No  
PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-matimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system systemSch100 No  
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth diameter-authSch1 No PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2 No PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs sgsSch1 No  
PPM,sgs,sgsSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-rej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-retx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-req-retx%,

sgs sgsSch2 No  
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs sgsSch3 No  
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-

tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME# configure

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 2

[local]MME(config-bulkstats-file-2)# no sgs

sgs - Removes sgs bulk statistics schema

[local]MME(config-bulkstats-file-2)# no sgs schema sgsSch1

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

|                             |                             |
|-----------------------------|-----------------------------|
| Server State:               | Enabled                     |
| File Limit:                 | 7500 KB                     |
| Sample Interval:            | 15 minutes (0D 0H 15M)      |
| Transfer Interval:          | 480 minutes (0D 8H 0M)      |
| Receiver Mode:              | Secondary-on-failure        |
| Historical Data Collection: | Enabled (15 samples stored) |

Bulk Statistics Server Statistics:

|                                |             |
|--------------------------------|-------------|
| Records awaiting transmission: | 0           |
| Bytes awaiting transmission:   | 0           |
| Total records collected:       | 0           |
| Total bytes collected:         | 0           |
| Total records transmitted:     | 0           |
| Total bytes transmitted:       | 0           |
| Total records discarded:       | 0           |
| Total bytes discarded:         | 0           |
| Last collection time required: | 0 second(s) |
| Last transfer time required:   | 0 second(s) |
| No successful data transfers   |             |
| No attempted data transfers    |             |

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0

Bytes awaiting transmission: 0

Total records collected: 0

Total bytes collected: 0

Total records transmitted: 0

Total bytes transmitted: 0

Total records discarded: 0

Total bytes discarded: 0

Last transfer time required: 0 second(s)

No successful data transfers

No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0

Bytes awaiting transmission: 0

Total records collected: 0

Total bytes collected: 0

Total records transmitted: 0

Total bytes transmitted: 0

Total records discarded: 0

Total bytes discarded: 0  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

| Type          | Name              | Active-Only | Format   |
|---------------|-------------------|-------------|--|
| system        | systemSch1        | No          | PPM,system,systemSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-ttlarrived%,%sess-ttlrejected%,%sess-ttlconnected%,%sess-ttlfailed%,%sess-ttldisconnect%,%sess-ttlhandoff%,%sess-ttlrenewal%,%sess-ttlcallop%,%sess-ttlauthsucc%,%sess-ttlauthfail%,%sess-curaaaactive%,%sess-curaaaadeleting%,%sess-curaaaacctpending%,%sess-curaaaacctitemsused%,%sess-curaaaacctitemsmax%,%sess-curaaaabuffused%,%sess-curaaaabuffmax%,%sess-ttlaaacancauth%,%sess-ttlaaaaacctpurged%,%sess-ttlradacctpurged%,%sess-ttllcpup%,   |
| system        | systemSch10       | No          | PPM,system,systemSch10,%epochtime%,%localdate%,%localtime%,%uptime%,%aaa-ttlpseudoauthreq%,%aaa-curpseudoauthreq%,%aaa-ttlauthnulluser%,%aaa-ttlacctsucc%,%aaa-ttlacctpurged%,%aaa-ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradacctreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradacctreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-matimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,   |
| system        | systemSch100      | No          | PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%, |
| diameter-auth | diameter-authSch1 | No          | PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-acpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,  |
| diameter-auth | diameter-authSch2 | No          | PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-acpt-rcvd%,%asr-req-rcvd%,%asa-rsp-acpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-   |

err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-  
authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%  
diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-  
protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-  
msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs sgsSch2 No  
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi  
d%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-  
rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-  
rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-  
rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs sgsSch3 No  
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servi  
d%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-  
retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-  
tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME# configure

[local]MME(config)# bulkstats mode

[local]MME(config-bulkstats)# file 2

[local]MME(config-bulkstats-file-2)# sgs schema sgsSch1 format PPM,sgs,sgsSch1,  
%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%serv  
id%,%pag-req-tx%,%pag-req-retx%,%pag-req-rx%,%pag-rej-tx%,%pag-rej-retx%,%pag-r  
ej-rx%,%service-req-tx%,%service-req-retx%,%service-req-rx%,%dl-ud-tx%,%dl-ud-r  
etx%,%dl-ud-rx%,%ul-ud-tx%,%ul-ud-retx%,%ul-ud-rx%,%localupd-req-tx%,%localupd-  
req-retx%,

[local]MME(config-bulkstats-file-2)# end

[local]MME# show bulkstats schemas

Bulk Statistics Server Configuration:

|                             |                             |
|-----------------------------|-----------------------------|
| Server State:               | Enabled                     |
| File Limit:                 | 7500 KB                     |
| Sample Interval:            | 15 minutes (0D 0H 15M)      |
| Transfer Interval:          | 480 minutes (0D 8H 0M)      |
| Receiver Mode:              | Secondary-on-failure        |
| Historical Data Collection: | Enabled (15 samples stored) |

Bulk Statistics Server Statistics:

Records awaiting transmission: 0

Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last collection time required: 0 second(s)  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 1

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0  
Bytes awaiting transmission: 0  
Total records collected: 0  
Total bytes collected: 0  
Total records transmitted: 0  
Total bytes transmitted: 0  
Total records discarded: 0  
Total bytes discarded: 0  
Last transfer time required: 0 second(s)  
No successful data transfers  
No attempted data transfers

File 2

Remote File Format: %date%-%time%

File Header: Version-20.0,%ipaddr%,%date%-%time%,%localdate%-%localtime%,%localtz%,%localtzoffset%,%localdate3%-%localtime3%,%swbuild%

File Footer: EndOfFile

No bulkstats receivers

File Statistics:

Records awaiting transmission: 0
Bytes awaiting transmission: 0
Total records collected: 0
Total bytes collected: 0
Total records transmitted: 0
Total bytes transmitted: 0
Total records discarded: 0
Total bytes discarded: 0
Last transfer time required: 0 second(s)
No successful data transfers
No attempted data transfers

File 3 not configured

File 4 not configured

----- Schemas for File 2-----

Table with 3 columns: Type, Name, Active-Only Format. It lists two system schemas: systemSch1 and systemSch10, each with a 'No' status and a list of various session-related metrics.

ttlacctcancelled%,%aaa-ttlacctkeepalivesuccess%,%aaa-ttlacctkeepalivetimeout%,%aaa-ttlacctkeepalivepurged%,%aaa-ttlradaccreq%,%aaa-ttlradacctcancelled%,%aaa-ttlradacctpurged%,%aaa-ttlradaccreqretried%,%aaa-ttlradacctrspdropped%,%aaa-ttlmgrpurgedrequests%,%diamauth-msg-mareq%,%diamauth-msg-maans%,%diamauth-msg-marretry%,%diamauth-msg-maamtimeout%,%diamauth-msg-maadropped%,%diamauth-msg-sareq%,

system systemSch100 No  
PPM,system,systemSch100,%epochtime%,%localdate%,%localtime%,%uptime%,%sess-bearerdur-24hr-qci6%,%sess-bearerdur-over24hr-qci6%,%sess-bearerdur-2day-qci6%,%sess-bearerdur-4day-qci6%,%sess-bearerdur-5day-qci6%,%sess-bearerdur-5sec-qci7%,%sess-bearerdur-10sec-qci7%,%sess-bearerdur-30sec-qci7%,%sess-bearerdur-1min-qci7%,%sess-bearerdur-2min-qci7%,%sess-bearerdur-5min-qci7%,%sess-bearerdur-15min-qci7%,%sess-bearerdur-30min-qci7%,%sess-bearerdur-1hr-qci7%,%sess-bearerdur-4hr-qci7%,%sess-bearerdur-12hr-qci7%,%sess-bearerdur-24hr-qci7%,%sess-bearerdur-over24hr-qci7%,%sess-bearerdur-2day-qci7%,%sess-bearerdur-4day-qci7%,%sess-bearerdur-5day-qci7%,

diameter-auth diameter-authSch1 No PPM,diameter-auth,diameter-authSch1,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%servertype%,%group%,%der-req-id-sent%,%der-req-aka-chal-sent%,%der-req-retried%,%dea-chal-rcvd%,%dea-acpt-rcvd%,%dea-timeout%,%dea-badauth%,%dea-malformed%,%dea-malformed-avp%,%dea-dropped%,%rar-req-rcvd%,%raa-ans-accpt-sent%,%aar-req-sent%,%str-req-sent%,%str-req-retried%,

diameter-auth diameter-authSch2 No PPM,diameter-auth,diameter-authSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%staans-accpt-rcvd%,%asr-req-rcvd%,%asa-rsp-accpt-sent%,%asa-rsp-rej-sent%,%req-sock-write-err%,%rsp-sock-write-err%,%any-sock-read-err%,%rem-disconnect%,%loc-disconnect%,

diameter-auth diameter-authSch3 No PPM,diameter-auth,diameter-authSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnid%,%vpnname%,%ipaddr%,%port%,%peer%,%diameter-auth-msg-multiround%,%diameter-auth-msg-success%,%diameter-auth-msg-err-protocol%,%diameter-auth-msg-err-transient%,%diameter-auth-msg-err-permanent%,%diameter-auth-msg-err-other%,%aaa-req-received%,%aaa-req-timeouts%,%aaa-req-dropped%,

sgs sgsSch2 No  
PPM,sgs,sgsSch2,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%localupd-req-rx%,%localupd-accept-tx%,%localupd-accept-retx%,%localupd-accept-rx%,%localupd-rej-tx%,%localupd-rej-retx%,%localupd-rej-rx%,%tmsi-reloc-tx%,%tmsi-reloc-retx%,%tmsi-reloc-rx%,%alert-req-tx%,%alert-req-retx%,%alert-req-rx%,%alert-ack-tx%,%alert-ack-retx%,%alert-ack-rx%,%alert-rej-tx%,%alert-rej-retx%,%alert-rej-rx%,%ue-actind-tx%,%ue-actind-retx%,

sgs sgsSch3 No  
PPM,sgs,sgsSch3,%epochtime%,%localdate%,%localtime%,%uptime%,%vpnname%,%vpnid%,%servname%,%servid%,%ue-actind-rx%,%eps-detind-tx%,%eps-detind-retx%,%eps-detind-rx%,%eps-detack-tx%,%eps-detack-retx%,%eps-detack-rx%,%imsi-detind-tx%,%imsi-detind-retx%,%imsi-detind-rx%,%imsi-detack-tx%,%imsi-detack-retx%,%imsi-detack-rx%,,,,,,,%mm-inforeq-tx%,%mm-inforeq-retx%,

[local]MME#

Szenario E. Das Ergebnis ist, wenn Sie das optionale Schlüsselwort verwenden. **Schemakönnen** Sie keine neuen Schemas hinzufügen. Sie können alle aktuellen Schemas (aus dem Knoten) löschen, aber sie nicht wieder hinzufügen. Die aktuellen Schemas in der Konfigurationsdatei (die in <url> vorhanden ist, werden von den Änderungen im Knoten nicht beeinflusst).

## Lösung

1. Das CLI **bulkstat-Konfigurationsschema** <url> wird verwendet, aufgrund dessen das Problem aufgetreten ist.
2. Es ist ein erwartetes Ergebnis pro Design, das Sie erhalten, wenn ein optionales Schlüsselwortschema verwendet wird.
3. Für diesen Fall gibt es drei Lösungen:

A. So entfernen Sie das cli **bulkstat-Konfigurationsschema <url>** und steuern das Hinzufügen/Löschen der Schemas über manuelle CLI/Eingabeaufforderung.

B. Zur Verwendung des optionalen Stichwortzusatzes in der bulkstat-Konfigurationscli. Mit der CLI **bulkstat-Konfigurationsergänzung <url>** können Sie den Schemas des aktuellen Knotens die in der Konfigurationsdatei vorhandenen Schemas hinzufügen. Sie können neue Schemas und aktuelle Schemas über die CLI-Eingabeaufforderung hinzufügen/löschen oder auch über die CLI-Eingabeaufforderung löschen.

C. Um die erforderlichen Schemas direkt in die Konfigurationsdatei hinzuzufügen/zu löschen und die Konfigurationen dann mit der Konfigurationsdatei neu zu laden (entfernen Sie zunächst die CLI durch **no bulkstat config**, fügen Sie die Schemas in die Konfigurationsdatei hinzu und fügen Sie sie dann durch das **bulkstats-Konfigurationsschema <url>**) zurück. Um die Schemas in die Konfigurationsdatei hinzuzufügen, können Sie sie entweder mit dem vi-Editor oder über SFTP mit der Datei ausführen

Mit dem vi-Editor:

```
[local]MME-01# cli test-commands password <pswd>
Warning: Test commands enables internal testing and debugging commands
USE OF THIS MODE MAY CAUSE SIGNIFICANT SERVICE INTERRUPTION

[local]MME-01# debug shell
Last log in: Wed Dec 22 15:05:12 +0530 2021 on pts/3 from 10.227.224.108.
MME-01:card1-cpu0# ls -lrtha

total 16
-r--r--r-- 1 root root 952 Dec 15 23:30 .rhosts
-r--r--r-- 1 root root 1.7K Dec 15 23:30 .gdbinit
drwx----- 2 root root 100 Dec 15 23:30 .ssh
drwxr-xr-x 24 root root 500 Dec 15 23:30 ..
-rw----- 1 root root 118 Dec 21 14:48 .bash_history
-rw-r--r-- 1 root root 1 Dec 22 15:05 file
drwxr-xr-x 3 root root 140 Dec 22 15:05 .

MME-01:card1-cpu0# vi file
```

SFTP der Konfigurationsdatei von <url> auf das lokale Laufwerk, bearbeiten Sie sie und setzen Sie sie zurück auf die <url>.