

Cisco Catalyst Center DN3

Contents

Product overview	3
Hardware specifications	3
Regulatory compliance	5
Scale	5
Supported Cisco Catalyst Center versions	6
Cisco Capital	6
How to buy	6
For more information	6

Product overview

Cisco Catalyst® Center is a powerful network management system that provides a centralized network management system for Cisco® networking devices.

Catalyst Center provides a single pane of glass for managing your entire Cisco enterprise network including switches, routers, and wireless access points.

Catalyst Center key capabilities

- **Automation** – Catalyst Center automates critical network tasks such as device deployment, configuration, software updates, and troubleshooting.
- **Deep Insights** – Leveraging AI, Catalyst Center provides insights and analytics to aid in optimizing end-user experience and security.
- **Zero-trust policy** – This solution helps identify threats and ensure network compliance to secure the enterprise.



Catalyst Center DN3s are a family of preconfigured hardware appliances designed to deliver enterprise-grade performance and simplified deployment of Catalyst Center. The appliances are available in three form factors to support the demands of different workloads. They all come with the Catalyst Center software pre-installed to help you get up and running quickly and efficiently.

The Catalyst Center DN3 appliances are based on Cisco UCS® C220 and UCS C240 servers and are configured specifically to support Catalyst Center.

Catalyst Center DN3 benefits:

- **Simplified deployment** – Preinstalled software accelerates setup and improves time to value.
- **Enhanced performance** – Powerful hardware delivers exceptional performance for demanding workloads.
- **Flexibility** – With three models to choose from, you can get the right appliance for your needs.

Hardware specifications

Physical specifications	DN3-HW-APL and DN3-HW-APL-L	DN3-HW-APL-XL
Image		
Hardware series	Cisco UCS C220 M6 Rack Server (data sheet)	Cisco UCS C240 M6 Rack Server (data sheet)
Form factor	1RU	2RU

Physical specifications	DN3-HW-APL and DN3-HW-APL-L	DN3-HW-APL-XL
Power supply	2 hot-pluggable, redundant 2300W titanium-certified AC	2 hot-pluggable, redundant 2300W titanium-certified AC
Physical dimensions	Height: 1.70 in. (4.3 cm) Width: 16.9 in. (42.9 cm) Depth: 18.9 in. (48.0 cm)	Height: 3.42 in. (8.7 cm) Width: 16.9 in. (42.9 cm) Depth: 18.9 in. (48.0 cm)
Operating temperature	Dry bulb temperature of 50°F to 95°F (10°C to 35°C)	Dry bulb temperature of 50°F to 95°F (10°C to 35°C)
Non-operating temperature	Dry-bulb temperature of -40°F to 149°F (-40°C to 65°C)	Dry-bulb temperature of -40°F to 149°F (-40°C to 65°C)
Operating humidity	10% to 90% and 82.4°F (28°C) maximum dew-point temperature, noncondensing environment	10% to 90% and 82.4°F (28°C) maximum dew-point temperature, noncondensing environment
Non-operating humidity	5% to 93% relative humidity, noncondensing, with a maximum wet-bulb temperature of 28°C across the 20°C to 40°C dry bulb range.	5% to 93% relative humidity, noncondensing, with a maximum wet-bulb temperature of 28°C across the 20°C to 40°C dry bulb range.
Operating altitude	A maximum elevation of 10,006 ft (3050 m)	A maximum elevation of 10,006 ft (3050 m)
Nonoperating altitude	An elevation of 0 to 39,370 ft (12,000 m)	An elevation of 0 to 39,370 ft (12,000 m)
Network and management I/O	Supported connectors: One 1 Gigabit Ethernet dedicated management port Two 1/10 Gigabit BASE-T Ethernet LAN ports One RS-232 serial port (RJ-45 connector) One 15-pin VGA2 connector Two USB 3.0 connectors One front-panel KVM connector that is used with a KVM cable, which provides two USB 2.0s, one VGA, and one serial (DB-9) connector	Supported connectors: One 1 Gigabit Ethernet dedicated management port Two 1/10 Gigabit BASE-T Ethernet LAN ports One RS-232 serial port (RJ-45 connector) One 15-pin VGA2 connector Three USB 3.0 connectors One front-panel KVM connector that is used with a KVM cable, which provides two USB 2.0s, one VGA, and one serial (DB-9) connector

Regulatory compliance

Parameter	Description
Regulatory compliance	Products should comply with CE markings per directives 2014/30/EU and 2014/35/EU
Safety	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1 GB4943 2001
EMC - Emissions	47CFR Part 15 (CFR 47) Class A AS/NZS CISPR32 Class A CISPR32 Class A EN55032 Class A ICES003 Class A VCCI Class A EN61000-3-2 EN61000-3-3 KN32 Class A CNS13438 Class A
EMC - Immunity	EN55024 CISPR24 EN300386 KN35

Scale

	DN3-HW-APL	DN3-HW-APL-L	DN3-HW-APL-XL
Devices¹ (non-fabric)	1000	2000	5000
Devices¹ (fabric)	2000	4000	8000
Access points (non-fabric)	4000	6000	13,000
Access points (fabric)	3000	4000	10,000

Notes:

¹ Switch, router, wireless controller. Switch stacks, Cisco StackWise[®] Virtual pairs, VSS pairs, and WLC HA SSO pairs each count as a single device.

Supported Cisco Catalyst Center versions

The DN3 appliances require Cisco Catalyst Center Release 2.3.7.5 or newer.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital® makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments.

[Learn more.](#)

How to buy

To view buying options and speak with a Cisco sales representative, visit www.cisco.com/c/en/us/buy.html.

For the Cisco Catalyst Center DN3 Ordering Guide, please see

<https://www.cisco.com/c/en/us/products/collateral/cloud-systems-management/dna-center/catalyst-formerly-gen-app-og.html>.

For more information

For more information, please visit the following resources:

- Cisco Catalyst Center: <https://www.cisco.com/go/CatalystCenter>
- Cisco Catalyst Center Software Data Sheet: <https://www.cisco.com/c/en/us/products/collateral/cloud-systems-management/dna-center/nb-06-dna-center-data-sheet-cte-en.html>

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)