

Configure and Verify VXLAN with MP-BGP EVPN Control Plane

Contents

[Introduction](#)

[Prerequisites](#)

[Requirements](#)

[Components Used](#)

[Background Information](#)

[Configure](#)

[Network Diagram](#)

[Configuration](#)

[VTEP1](#)

[VTEP2](#)

[VTEP3](#)

[VTEP4](#)

[SPINE](#)

[HOST A](#)

[HOST B](#)

[HOST C and D](#)

[Verify](#)

[Connectivity from Host A to External Host B](#)

[Connectivity from Host A to HOST C \(Intra-VNI\)](#)

[Connectivity from Host A to HOST D \(Inter-VNI\)](#)

[Routing Table of Host B \(External Peer\)](#)

[Verification of Control-Plane](#)

[Troubleshoot](#)

Introduction

This document describes the VXLAN configuration using MP-BGP EVPN control-plane.

Prerequisites

Requirements

Cisco recommends that you have knowledge of these topics:

- MPLS Layer 3 VPNs
- MP-BGP would also help.

Components Used

This document is not restricted to specific software and hardware versions.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, ensure that you understand the potential impact of any command.

Background Information

This document also shows a sample network scenario and its configuration with relevant outputs for verification and better understanding.

VXLAN is designed to provide network virtualization. It is MAC in UDP encapsulation. Layer 2 infrastructure is extended over Layer 3 underlay network to provide a simplified service which is not dependent on physical and geographical location of servers in the datacenters.

This document describes VXLAN with MP-BGP EVPN Control Plane. This means that BGP protocol is used in overlay infrastructure to send and receive updates.

In traditional network deployments STP was used, this resulted in some uplinks permanently blocking state. In VXLAN design all the uplinks are operational and ECMP is leveraged as underlay infrastructure is IP network.

Discussion of all the details is outside the scope of this document, however some important terminologies are shown below.

VXLAN - Virtual Extensible LAN

MP-BGP - Multiprotocol BGP

EVPN - Ethernet VPN


VTEP - Virtual Tunnel End Point. Also known as the leaf. This is the place where the packets are encapsulated and decapsulated.

Spine - This is very similar to Route-Reflector in MPLS L3 VPNs. This device takes the updates from one VTEP and passes on it to other VTEP.

VNI - VXLAN Network Identifier. This is mainly used to provide isolation for layer-2 boundaries. This field is 24 bit in length so it overcomes the range limitation of traditional vlans. A VNI in a VTEP is mapped to a traditional vlan. This is discussed later.

Configure

Network Diagram



The image shown is used for configuration and verification aspects. This covers non-vpc, vpc, intra-vni, inter-vni and external connectivity configurations from the perspective of VXLAN infrastructure.

Configuration

VTEP1

```
<#root>
```

```
!
```

Enabling features

```
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan
feature vn-segment-vlan-based
```

```
feature lACP
feature vpc
feature nv overlay
```

```
!
```

```
fabric forwarding anycast-gateway-mac 0001.0001.0001
```

```
!
```

```
This is needed for seamless VM mobility across VTEPS,
this configuration is same on all VTEPS.
```

```
ip pim rp-address 192.168.9.9 group-list 224.0.0.0/4
```

```
! SPINE is the RP.
```

```
!
```

```
ip pim ssm range 232.0.0.0/8
```

```
!
```

```
vlan 1,10,30,40,100,200
```

```
!
```

```
vlan 10
```

```
!
```

```
VLAN 10 is used as layer3 VNI to route Inter-VNI traffic.
```

```
name L3-VNI-VLAN-10
vn-segment 10000010
vlan 30
```

```
! The Host A resides on Vlan 30, The below command 'maps' vlan 30 with VNID 10000030.
```

```
vn-segment 10000030
```

```
!
```

```
vrf context EVPN-L3-VNI-VLAN-10
```

```
! Defining layer3 vrf for Inter-VNI traffic.
```

```
vni 10000010
rd auto
address-family ipv4 unicast
route-target both auto
route-target both auto evpn
```

```
!
```

```
interface Vlan10
```

```
! Layer3 VNI associated interface vlan does not have an ip address.
```

```
no shutdown
```

```
vrf member EVPN-L3-VNI-VLAN-10
ip forward
```

```
!
```

```
interface Vlan30
```

```
! Associating the Host A Vlan with layer3 vrf.
```

```
no shutdown
vrf member EVPN-L3-VNI-VLAN-10
ip address 172.16.30.1/24
fabric forwarding mode anycast-gateway
```

```
!
```

```
This is needed for seamless VM mobility across VTEPS, same on all VTEPS.
```

```
!
```

```
interface nve1
```

```
! Nve is logical interface where VXLAN packets are encapsulated and decapsulated.
```

```
no shutdown
source-interface loopback2
host-reachability protocol bgp
```

```
! This means BGP control plane is used to exchange updates.
```

```
member vni 10000010 associate-vrf
```

```
! associate-vrf is used for for layer3 vni.
```

```
member vni 10000030
suppress-arp
mcast-group 239.1.1.10
```

```
! A vlan or set of vlans mapped to VNI can be given identical multicast address, this is used for control
```

```
!
```

```
interface Ethernet1/2
```

```
! Ospf with PIM is used as Underlay.
```

```
description "Going to Spine"
no switchport
ip address 192.168.19.1/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
!
```

```
interface Ethernet1/11
```

! Port to Host A.

```
switchport mode trunk
```

!

```
interface loopback2 !
```

Loopback for BGP Peering.

```
description "Loopback for "BGP"  
ip address 192.168.11.11/32  
ip router ospf UNDERLAY area 0.0.0.0  
ip pim sparse-mode
```

!

```
router ospf UNDERLAY
```

!

```
router bgp 65000  
address-family ipv4 unicast  
address-family l2vpn evpn  
neighbor 192.168.9.9
```

!

Peering with SPINE.

```
remote-as 65000  
update-source loopback2  
address-family ipv4 unicast  
address-family l2vpn evpn  
send-community extended  
vrf EVPN-L3-VNI-VLAN-10  
address-family ipv4 unicast  
advertise l2vpn evpn
```

!

```
evpn  
vni 10000030 l2  
rd auto
```

! RD is default calculated as VNI:BGP Router ID

```
route-target import auto
```

! RT is default calculated as BGP AS:VNI

```
route-target export auto
```

VTEP2

<#root>

```
!  
  
nv overlay evpn  
feature ospf  
feature bgp  
feature pim  
feature interface-vlan  
feature vn-segment-vlan-based  
feature lacp  
feature vpc  
feature nv overlay  
  
!  
  
fabric forwarding anycast-gateway-mac 0001.0001.0001  
  
!  
ip pim rp-address 192.168.9.9 group-list 224.0.0.0/4  
  
!  
ip pim ssm range 232.0.0.0/8  
vlan 1,10,30,40,100  
  
!  
vlan 10  
  
! This VTEP is dedicated for external connectivity, there is only layer3 VNI config.  
  
name L3-VNI-VLAN-10  
vn-segment 10000010  
  
!  
vrf context EVPN-L3-VNI-VLAN-10  
  
! Defining layer3 vrf for Inter-VNI traffic.  
  
vni 10000010  
rd auto  
address-family ipv4 unicast  
route-target both auto  
route-target both auto evpn  
  
!  
interface Vlan10  
  
! Layer3 VNI associated interface vlan does not have an ip address.  
  
no shutdown  
vrf member EVPN-L3-VNI-VLAN-10  
ip forward  
  
!  
interface Vlan100  
  
! This vlan is used to peer with external EBGp Peer.  
  
no shutdown
```

```
vrf member EVPN-L3-VNI-VLAN-10
ip address 192.168.1.2/24
```

```
!
```

```
interface nve1
no shutdown
source-interface loopback2
host-reachability protocol bgp
member vni 10000010 associate-vrf
```

```
!
```

```
interface Ethernet1/2
```

```
! Ospf and PIM are used in Underlay.
```

```
description "Going to Spine"
no switchport
ip address 192.168.29.2/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
!
```

```
interface Ethernet1/12
```

```
! Port to External Peer.
```

```
switchport mode trunk
```

```
!
```

```
interface loopback2
ip address 192.168.22.22/32
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
```

```
!
```

```
router ospf UNDERLAY
```

```
!
```

```
router bgp 65000
address-family ipv4 unicast
address-family l2vpn evpn
neighbor 192.168.9.9
```

```
! Peering with SPINE.
```

```
remote-as 65000
update-source loopback2
address-family ipv4 unicast
address-family l2vpn evpn
send-community extended
vrf EVPN-L3-VNI-VLAN-10
address-family ipv4 unicast
advertise l2vpn evpn
neighbor 192.168.1.1
```



```
! Peering with External Peer, under vrf.
```

```
remote-as 65111  
update-source Vlan100  
address-family ipv4 unicast
```

VTEP3

The configs for VTEP3 and VTEP1 are almost identical. Only difference is VPC and an additional layer2 VNI for vlan 40.

```
<#root>
```

```
!
```

```
nv overlay evpn  
feature ospf  
feature bgp  
feature pim  
feature interface-vlan  
feature vn-segment-vlan-based  
feature lacp  
feature vpc  
feature nv overlay
```

```
!
```

```
fabric forwarding anycast-gateway-mac 0001.0001.0001
```

```
!
```

```
ip pim rp-address 192.168.9.9 group-list 224.0.0.0/4
```

```
!
```

```
ip pim ssm range 232.0.0.0/8
```

```
!
```

```
vlan 1,10,20,30,40
```

```
!
```

```
vlan 10  
name L3-VNI-VLAN-10  
vn-segment 10000010
```

```
!
```

```
vlan 30  
vn-segment 10000030
```

```
!
```

```
vlan 40
```

```
!
```

```
New host vlan 40.
```

```
vn-segment 10000040
```

```
!  
vpc domain 2  
!  
! Vpc Configs.  
  
peer-keepalive destination 10.197.204.103 source 10.197.204.106  
  
!  
interface Vlan10  
no shutdown  
vrf member EVPN-L3-VNI-VLAN-10  
ip forward  
  
!  
interface Vlan30  
no shutdown  
vrf member EVPN-L3-VNI-VLAN-10  
ip address 172.16.30.1/24  
  
!  
fabric forwarding mode anycast-gateway  
  
!  
interface Vlan40  
no shutdown  
vrf member EVPN-L3-VNI-VLAN-10  
ip address 172.16.40.1/24  
  
!  
fabric forwarding mode anycast-gateway  
  
!  
interface port-channel2  
switchport mode trunk  
vpc 2  
  
!  
interface port-channel34  
switchport mode trunk  
spanning-tree port type network  
vpc peer-link  
  
!  
interface nve1  
no shutdown  
source-interface loopback2  
host-reachability protocol bgp  
member vni 10000010 associate-vrf  
member vni 10000030  
suppress-arp  
mcast-group 239.1.1.10  
member vni 10000040  
  
!
```

New layer2 VNI for Vlan 40.

```
suppress-arp
mcast-group 239.1.1.20
```

!

```
interface Ethernet1/1
```

! Connected to VTEP4.

```
switchport mode trunk
channel-group 34 mode active
```

!

```
interface Ethernet1/2
```

```
description "going to Spine"
```

```
no switchport
```

```
ip address 192.168.39.3/24
```

```
ip router ospf UNDERLAY area 0.0.0.0
```

```
ip pim sparse-mode
```

```
no shutdown
```

!

```
interface Ethernet1/13
```

! Connected to N5K, which simulates Host C and D.

```
switchport mode trunk
channel-group 2 mode active
```

!

```
interface loopback2
```

```
description "loopback for Bgp"
```

```
ip address 192.168.33.33/32
```

```
ip address 192.168.33.34/32 secondary
```

!

For other VTEPs VTEP3 and VTEP4 look as single entity.

```
ip router ospf UNDERLAY area 0.0.0.0
```

!

This secondary address is needed in Vpc designs.

!

```
router ospf UNDERLAY
```

!

```
router bgp 65000
```

```
address-family ipv4 unicast
```

```
address-family l2vpn evpn
neighbor 192.168.9.9 remote-as 100
remote-as 65000
update-source loopback2
address-family ipv4 unicast
address-family l2vpn evpn
send-community extended
vrf EVPN-L3-VNI-VLAN-10
address-family ipv4 unicast
advertise l2vpn evpn
```

```
!
evpn
vni 10000030 l2
rd auto
route-target import auto
route-target export auto
vni 10000040 l2
rd auto
route-target import auto
route-target export auto
```

VTEP4

```
<#root>
```

```
!
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
!
fabric forwarding anycast-gateway-mac 0001.0001.0001
!
ip pim rp-address 192.168.9.9 group-list 224.0.0.0/4
!
ip pim ssm range 232.0.0.0/8
!
vlan 1,10,20,30,40
!
vlan 10
name L3-VNI-VLAN-10
vn-segment 10000010
!
vlan 30
vn-segment 10000030
```

```
!  
vlan 40  
  vn-segment 10000040  
  
!  
vrf context EVPN-L3-VNI-VLAN-10  
  vni 10000010  
  rd auto  
  address-family ipv4 unicast  
  route-target both auto  
  route-target both auto evpn  
  
!  
  
interface Vlan10  
  no shutdown  
  vrf member EVPN-L3-VNI-VLAN-10  
  ip forward  
  
!  
  
interface Vlan30  
  no shutdown  
  vrf member EVPN-L3-VNI-VLAN-10  
  ip address 172.16.30.1/24  
  
!  
  fabric forwarding mode anycast-gateway  
  
!  
  
interface Vlan40  
  no shutdown  
  vrf member EVPN-L3-VNI-VLAN-10  
  ip address 172.16.40.1/24  
  
!  
  fabric forwarding mode anycast-gateway  
  
!  
  
interface port-channel2  
  switchport mode trunk  
  vpc 2  
  
!  
  
interface port-channel34  
  switchport mode trunk  
  spanning-tree port type network  
  vpc peer-link  
  
!  
  
interface nve1  
  no shutdown  
  source-interface loopback2  
  host-reachability protocol bgp  
  member vni 10000010 associate-vrf  
  member vni 10000030  
  suppress-arp
```

```
mcast-group 239.1.1.10
member vni 10000040
suppress-arp
mcast-group 239.1.1.20
```

!

```
interface Ethernet1/1
```

```
! Connected to VTEP3.
```

```
switchport mode trunk
channel-group 34 mode active
```

!

```
interface Ethernet1/2
```

```
description "going to spine"
no switchport
ip address 192.168.49.4/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

!

```
interface Ethernet1/13
```

```
! Connected to N5K, which simulates Host C and D.
```

```
switchport mode trunk
channel-group 2 mode active
```

!

```
router ospf UNDERLAY
```

!

```
router bgp 65000
address-family ipv4 unicast
address-family l2vpn evpn
neighbor 192.168.9.9 remote-as 100
remote-as 65000
update-source loopback2
address-family ipv4 unicast
address-family l2vpn evpn
send-community extended
vrf EVPN-L3-VNI-VLAN-10
address-family ipv4 unicast
advertise l2vpn evpn
```

!

```
evpn
vni 10000030 l2
rd auto
route-target import auto
route-target export auto
vni 10000040 l2
rd auto
route-target import auto
route-target export auto
```

SPINE

<#root>

!

```
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
```

!

```
ip pim rp-address 192.168.9.9 group-list 224.0.0.0/4
```

!

```
ip pim ssm range 232.0.0.0/8
```

!

```
interface Ethernet1/1
```

```
! To VTEP1.
```

```
ip address 192.168.19.9/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

!

```
interface Ethernet1/2
```

```
! To VTEP2.
```

```
ip address 192.168.29.9/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

!

```
interface Ethernet1/3
```

```
! To VTEP3.
```

```
ip address 192.168.39.9/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

!

```
interface Ethernet1/4
```

! To VTEP4.

```
ip address 192.168.49.9/24
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
no shutdown
```

!

interface loopback1

! SPINE is RP(Rendezvous Point).

```
ip address 192.168.9.9/32
ip router ospf UNDERLAY area 0.0.0.0
ip pim sparse-mode
```

!

router ospf UNDERLAY

!

```
router bgp 65000
log-neighbor-changes
address-family ipv4 unicast
address-family l2vpn evpn
retain route-target all
template peer VTEP-PEERS
remote-as 65000
update-source loopback1
address-family ipv4 unicast
send-community both
route-reflector-client
```

! Spine treats VTEPs as Route-Reflector Clients.

```
address-family l2vpn evpn
send-community both
route-reflector-client
neighbor 192.168.11.11
```

! VTEP1.

```
inherit peer VTEP-PEERS
neighbor 192.168.22.22
```

! VTEP2.

```
inherit peer VTEP-PEERS
neighbor 192.168.33.33
```

! VTEP3.

```
inherit peer VTEP-PEERS
neighbor 192.168.44.44
```

! VTEP4.

```
inherit peer VTEP-PEERS
```


HOST A

Host A is simulated by a 3750 Switch.

```
<#root>
! This port is the uplink to VTEP1.

interface GigabitEthernet1/0/1
  switchport trunk encapsulation dot1q
  switchport mode trunk

!

interface Vlan30
  ip address 172.16.30.33 255.255.255.0

!

! Below the default route to VTEP1.

ip route 0.0.0.0 0.0.0.0 172.16.30.1
```

HOST B

Host B is the external peering device. N5K is used here.

```
<#root>
!

router bgp 65111
  address-family ipv4 unicast

!
  network 172.16.2.2/32

!

Advertsing the external subnet to VXLAN infrastructure.

  neighbor 192.168.1.2 remote-as 65000

!

EBGP Peering with VTEP2.

  address-family ipv4 unicast

!
```

```
interface loopback1
  ip address 172.16.2.2/32

!

interface Ethernet1/19

!

Uplink port to VTEP2.

  switchport mode trunk

!

interface Vlan100
  no shutdown
  ip address 192.168.1.1/24
```

HOST C and D

Host C and D are simulated by Nexus5k , keeping the ip addresses in distinct vrf.

```
<#root>

!

vrf context vni30

!

This vrf simulates the HOST C.

  ip route 0.0.0.0/0 172.16.30.1
vrf context vni40

! This vrf simulates the HOST D.

  ip route 0.0.0.0/0 172.16.40.1

!

interface Vlan30

! Addressing for HOST C.

  no shutdown
vrf member vni30
  ip address 172.16.30.2/24

!

interface Vlan40

! Addressing for HOST D.
```

```
no shutdown
vrf member vni40
ip address 172.16.40.2/24

!

interface Ethernet1/20

! Uplink port to VTEP3 in Port-Channel.

switchport mode trunk
channel-group 2 mode active

!

interface Ethernet1/21

! Uplink port to VTEP4 in Port-Channel.

switchport mode trunk
channel-group 2 mode active< /pre>
```

Verify

Connectivity from Host A to External Host B

```
HOST_A#ping 172.16.2.2
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.2.2, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/4/9 ms
```

Connectivity from Host A to HOST C (Intra-VNI)

```
HOST_A#ping 172.16.30.2
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.30.2, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/4/9 ms
```

Connectivity from Host A to HOST D (Inter-VNI)

```
HOST_A#ping 172.16.40.2

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.40.2, timeout is 2 seconds:
```

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/9 ms

Routing Table of Host B (External Peer)

<#root>

```
N5K-5672-1# show ip route bgp
IP Route Table for VRF "default"
'*' denotes best ucast next-hop
 '**' denotes best mcast next-hop
 '[x/y]' denotes [preference/metric]
 '%<string>' in via output denotes VRF <string>
```

```
172.16.30.2/32, ubest/mbest: 1/0, pending
```

! Host route for Host C.

```
*via 192.168.1.2, [20/0], 00:00:22, bgp-65100, external, tag 65000,
172.16.30.33/32, ubest/mbest: 1/0, pending
```

! Host route for Host A.

```
*via 192.168.1.2, [20/0], 00:00:22, bgp-65100, external, tag 65000,
172.16.40.2/32, ubest/mbest: 1/0, pending
```

! Host route for Host D.

```
*via 192.168.1.2, [20/0], 00:00:22, bgp-65100, external, tag 65000,
```

It can be observed that the host routes have been successfully advertised to this external BGP peer.

Verification of Control-Plane

- This command shows the mapping of traditional vlans with VNIDs.

```
VTEP1# show vxlan
Vlan VN-Segment
==== =====
10 10000010
30 10000030
40 10000040
```

- The next is to check that mac is learned locally on VTEP.

<#root>

```
VTEP1# show mac address-table vlan 30
Legend:
```

* - primary entry, G - Gateway MAC, (R) - Routed MAC, O - Overlay MAC
 age - seconds since last seen,+ - primary entry using vPC Peer-Link,
 (T) - True, (F) - False
 VLAN MAC Address Type age Secure NTFY Ports

-----+-----+-----+-----+-----+-----+-----+-----

```
*
30 0006.f63f.e3c1 dynamic 0 F F Eth1/11 ! Mac of HOST A
* 30 8c60.4ff2.f541 dynamic 0 F F nve1(192.168.33.34)

! Mac of HOST C installed into mac address table, it was learned from BGP.

G 30 e00e.da2a.2393 static - F F sup-eth1(R)
```

- Next step is to check that the route is installed into l2rib.

<#root>

```
VTEP1# show l2route evpn mac evi 30
Mac Address Prod Next Hop (s)
```

```
0006.f63f.e3c1
Local Eth1/11
! Mac of HOST A
i
ninstalled into l2rib.
```

```
8c60.4ff2.f541
BGP 192.168.33.34
! Mac of HOST C installed into l2rib learnt via BGP.
```

<#root>

```
VTEP1# show l2route evpn
mac-ip
evi 30
Mac Address Prod Host IP Next Hop (s)
```

```
0006.f63f.e3c1 HMM 172.16.30.33 N/A
8c60.4ff2.f541
BGP
172.16.30.2
192.168.33.34
```

! Mac+IP of Host C learnt across the Vxlan Fabric.

<#root>

VTEP1# show l2route evpn

mac-ip

evi 40

Mac Address Prod Host IP Next Hop (s)

8c60.4ff2.f541

BGP

172.16.40.2

192.168.33.34

! Mac+IP of Host D learnt across the Vxlan Fabric.

- Next step is to check that l2rib exports the update to l2vpn evpn.

VTEP1# show bgp l2vpn evpn vni-id 10000030

BGP routing table information for VRF default, address family L2VPN EVPN

BGP table version is 31, local router ID is 192.168.11.11

Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-i
njected

Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup

<#root>

Network Next Hop Metric LocPrf Weight Path

Route Distinguisher: 192.168.11.11:32797 (L2VNI 10000030)

*>l[2]:[0]:[0]:[48]:[

0006.f63f.e3c1

]:[0]:[0.0.0.0]/216

!

Mac of Host A in update.

192.168.11.11 100 32768 i

*>i[2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[0]:[0.0.0.0]/216

192.168.33.34 100 0 i

* i 192.168.33.34 100 0 i

*>l[2]:[0]:[0]:[48]:[

```
0006.f63f.e3c1
```

```
]:[32]:[
```

```
172.16.30.33
```

```
]/272
```

```
!
```

Mac and IP of Host A in update.

```
192.168.11.11 100 32768 i
```

```
* i[2]:[0]:[0]:[48]:[
```

```
8c60.4ff2.f541
```

```
]:[32]:[
```

```
172.16.30.2
```

```
]/272
```

```
!
```

Mac and IP of Host C in update from

Spine.

```
192.168.33.34 100 0 i
```

```
*>i 192.168.33.34 100 0 i
```

- Next step is to check that the routes are advertised to Spine.

```
VTEP1# show bgp l2vpn evpn nei 192.168.9.9 advertised-routes
```

```
Peer 192.168.9.9 routes for address family L2VPN EVPN:
```

```
BGP table version is 31, local router ID is 192.168.11.11
```

```
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
```

```
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-i
```

```
njected
```

```
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup
```

```
<#root>
```

```
Network Next Hop Metric LocPrf Weight Path
```

```
Route Distinguisher: 192.168.11.11:32797 (L2VNI 10000030)
```

```
*>l[2]:[0]:[0]:[48]:[0006.f63f.e3c1]:[0]:[0.0.0.0]/216
```

```
192.168.11.11 100 32768 i
```

```
*>l[2]:[0]:[0]:[48]:[
```

```
0006.f63f.e3c1
```

```
]:[32]:[
```

172.16.30.33

]/272

! Mac and IP advertised to Spine.

192.168.11.11 100 32768 i

- Next step is to check the routes received from Spine.

<#root>

VTEP1# show bgp l2vpn evpn nei 192.168.9.9 routes

Peer 192.168.9.9 routes for address family L2VPN EVPN:
BGP table version is 31, local router ID is 192.168.11.11
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup

Network Next Hop Metric LocPrf Weight Path
Route Distinguisher: 192.168.11.11:32797 (L2VNI 10000030)
*>i[2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[0]:[0.0.0.0]/216
192.168.33.34 100 0 i
* i 192.168.33.34 100 0 i
* i[2]:[0]:[0]:[48]:[

8c60.4ff2.f541

]:[32]:[

172.16.30.2

]/272

! This is update from Host C in same VNID.

192.168.33.34 100 0 i
*>i 192.168.33.34 100 0 i

Route Distinguisher: 192.168.11.11:32807 (L2VNI 10000040)
*>i[2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[0]:[0.0.0.0]/216
192.168.33.34 100 0 i
* i 192.168.33.34 100 0 i
* i[2]:[0]:[0]:[48]:[

8c60.4ff2.f541

]:[32]:[

172.16.40.2

]/272

!

This is update from Host D in different VNID.

192.168.33.34 100 0 i


```
*>i 192.168.33.34 100 0 i
```

```
Route Distinguisher: 192.168.11.11:3 (L3VNI 10000010)
```

```
*>i[2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[32]:[172.16.30.2]/272  
192.168.33.34 100 0 i
```

```
* i 192.168.33.34 100 0 i
```

```
*>i[2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[32]:[172.16.40.2]/272  
192.168.33.34 100 0 i
```

```
* i 192.168.33.34 100 0 i
```

```
*>i[5]:[0]:[0]:[32]:[
```

```
172.16.2.2
```

```
]:[0.0.0.0]/224 !
```

```
! This is update from External Host.
```

```
192.168.22.22 100 0 65100 i
```

```
<#root>
```

```
VTEP1# show ip bgp vrf
```

```
EVPN-L3-VNI-VLAN-10
```

```
BGP routing table information for VRF EVPN-L3-VNI-VLAN-10, address family IPv4 Unicast  
BGP table version is 5, local router ID is 192.168.1.254  
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best  
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected  
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup
```

```
Network          Next Hop Metric LocPrf Weight Path
```

```
*>i
```

```
172.16.2.2/32
```

```
192.168.22.22 100 0 65111 i
```

```
*>i
```

```
172.16.30.2/32
```

```
192.168.33.34 100 0 i  
* i 192.168.33.34 100 0 i
```

```
*>i
```

```
172.16.40.2/32
```

```
192.168.33.34 100 0 i  
* i 192.168.33.34 100 0 i
```

- In VTEP1, only VNID 10000030 is configured, and it has been verified that mac and ip of Host A are learned locally, and also advertised as evpn route. It has also been observed that the update from Host C has also been received and installed here.

- The nve peers can also be up before the traffic can be forwarded.

<#root>

VTEP1# show nve peers

Interface Peer-IP State LearnType Uptime Router-Mac

nve1

192.168.22.22

Up CP 01:39:15 0062.ecbf.5325

!

VTEP2

nve1

192.168.33.34

Up CP 01:40:09 f8c2.8823.275f

!

VTEP3 and VTEP4 appear as single entity as both are in Vpc.

<#root>

VTEP1# sh bgp internal nve-peer-vni

PeerAddress VNI VrfID GatewayMAC TunnelID Encap EgressVNI F

192.168.22.22

10000010 1

0062.ecbf.5325

0xc0a81616

1 0 0

192.168.33.34

10000010 1

0062.ecbf.4e4d

0xc0a82122

1 0 0

192.168.33.34 10000010 1 f8c2.8823.275f 0xc0a82122 1 0 0

192.168.33.34 10000030 1 0000.0000.0000 0x0 1 0 0

192.168.33.34 10000040 1 0000.0000.0000 0x0 1 0 0

Troubleshoot

- If nve interface is checked, then increments of counters for encapsulation and decapsulation can be seen.

```
<#root>
```

```
VTEP1# show interface nve 1
nve1 is up
admin state is up, Hardware: NVE
```

```
MTU 9216 bytes
```

```
Encapsulation VXLAN
Auto-mdix is turned off
```

```
RX
```

```
ucast: 133 pkts, 22344 bytes - mcast: 0 pkts, 0 bytes
```

```
TX
```

```
ucast: 134 pkts, 22512 bytes - mcast: 0 pkts, 0 bytes
```

- If a transparent firewall is being used for filtering, make the sure the associated port is allowed.

```
<#root>
```

```
VTEP1# show nve vxlan-params
```

```
VxLAN Dest. UDP Port: 4789
```

- To check the local VTEP mac address which is used for Inter-VNI routing. Secondary address is seen when the VTEP is in a vpc pair.

```
<#root>
```

```
VTEP1# show nve interface
```

```
Interface: nve1, State: Up, encapsulation: VXLAN
```

```
VPC Capability: VPC-VIP-Only [not-notified]
```

```
Local Router MAC: e00e.da2a.2393
```

```
Host Learning Mode: Control-Plane
```

```
Source-Interface: loopback2 (primary: 192.168.11.11, secondary: 0.0.0.0)
```

- To check the remote VTEPS mac addresses and state of peering.

<#root>

VTEP1# sh nve internal platform interface nve1 detail

Printing Interface ifindex 0x49000001 detail

Intf	State	PriIP	SecIP	Vnis	Peers
nve1	UP	192.168.11.11			

0.0.0.0

|3 |2 | !

Secondary Ip is 0.0.0.0 because this VTEP is not in vpc

SW_BD/VNIs of interface nve1:

Sw BD	Vni	State	Intf	Type	Vrf-ID	Notified
10	10000010	UP	nve1	CP	3	Yes
30	10000030	UP	nve1	CP	0	Yes
40	10000040	UP	nve1	CP	0	Yes

10 |10000010|UP |nve1 |CP |3 |Yes

|30 |10000030|UP |nve1 |CP |0 |Yes

40 |10000040|UP |nve1 |CP |0 |Yes

Peers of interface nve1:

Peer_ip: 192.168.22.22
Peer-ID : 1
State : UP
Learning : Disabled
TunnelID : 0xc0a81616

MAC : 0062.ecbf.5325

Table-ID : 0x1
Encap : 0x1

Peer_ip: 192.168.33.34 ! For both VTEP3 and VTEP4
Peer-ID : 2
State : UP
Learning : Disabled
TunnelID : 0xc0a82122

MAC : 0062.ecbf.4e4d

Table-ID : 0x1
Encap : 0x1

- To check the peering time and VNI information for VTEP Peers.

```
VTEP1# show nve peer detail
Details of nve Peers:
-----

Peer-IP: 192.168.22.22
NVE Interface : nve1
Peer State : Up
Peer Uptime : 00:22:17

Router-Mac : 0062.ecbf.5325
Peer First VNI : 10000010
Time since Create : 00:22:17

Configured VNIs : 10000010,10000030,10000040
Provision State : add-complete ! Hardware ready for forwarding.
Route-Update : Yes
Peer Flags : RmacL2Rib, TunnelPD, DisableLearn
Learnt CP VNIs : 10000010
Peer-ifindex-resp : Yes
-----

Peer-IP: 192.168.33.34
NVE Interface : nve1
Peer State : Up
Peer Uptime : 00:22:10
Router-Mac : 0062.ecbf.4e4d
Peer First VNI : 10000010
Time since Create : 00:22:10
Configured VNIs : 10000010,10000030,10000040
Provision State : add-complete ! Hardware ready for forwarding.
Route-Update : Yes
Peer Flags : RmacL2Rib, TunnelPD, DisableLearn
Learnt CP VNIs : 10000010,10000030,10000040
Peer-ifindex-resp : Yes
-----
```

- To check how BGP interacts with EVI and internal information is built. Example of vlan 30 mapped to VNI 10000030 is shown here.

```
<#root>
```

```
VTEP1#
```

```
sh bgp internal evi 10000030
```

```
*****
L2RIB bound / VNI Req to L2RIB : Yes / 1
L2VNI Adds / Dels / ALL Dels from L2RIB : 4 / 3 / 1
First L2VNI Add/Del : Dec 17 19:07:41.680736 / Dec 17 19:10:48.455562
Last L2VNI Add/Del : Dec 17 19:11:13.916893 / Dec 17 19:10:48.455792
L3VNI Adds / Dels from L2RIB : 2 / 0 / 1
First L3VNI Add/Del : Dec 17 19:07:41.681313 / never
Last L3VNI Add/Del : Dec 17 19:11:11.838315 / never
First/Last All VNI Del : Dec 17 19:10:48.455542 / Dec 17 19:10:48.455543
```

ALL VNI Del from L2RIB state (cleanup status) : All VNI Not Start (0x000006)
All VNI down loop count : 0
L2RIB is up/registered/local-req: 1/1
L2RIB down: in-prg/up-defer: 0/0
L2RIB register/failures: 1/0
L2RIB deregister/failures: 0/0
L2RIB flow control (#enabled/#disabled): Disabled (0/0)

BGP L2VPN/EVPN RD Information for 192.168.11.11:32797

L2VNI ID : 10000030 (evi_10000030)
#Prefixes Local/BRIB : 2 / 4
#Paths L3VPN->EVPN/EVPN->L3VPN : 129 / 0

=====
BGP Configured VNI Information:

evi_cfg : 0xd87786c8

VNI ID (Index) : 10000030

(1)

RD : 192.168.11.11:32797

Export RTs : 1

ExportRT cfg list:
65000:10000030 (auto)
Import RTs : 1
ImportRT cfg list:
65000:10000030 (auto)
Topo Id : 30

VTEP IP : 192.168.11.11

VTEP VPC IP : 0.0.0.0
Encap Type : 8
RefCount : #00000003

Enabled : Yes ! If this is no then check the NVE interface config for this VNID

Delete Pending : No
Creation Req : No
Future RD : NULL
evi_ctx : 0xd86e554c
RD/Import RT/Export RT : Yes(Auto)/Yes/Yes
MAC First Add/Del : Dec 17 19:11:12.45086 / never
MAC Last Add/Del : Dec 17 19:11:12.45086 / never
MAC IP First Add/Del : Dec 17 19:11:12.54976 / never
MAC IP Last Add/Del : Dec 17 19:11:12.54977 / never
IMET First Add/Del : never / never
IMET Last Add/Del : never / never

=====
++++
BGP VNI Information for evi_10000030 (0xd86e554c)
L2VNI ID : 10000030 (evi_10000030)
RD (rdinfo) : 192.168.11.11:32797 (0xd8811eb0)

Prefixes (local/total) : 2/4
Created : Dec 17 19:11:12.37640
Last Oper Up/Down : Dec 17 19:11:12.37827 / never
Enabled : Yes
Delete pending : 0
Stale : No
Import pending : 0
Import in progress : 0
Encap : VxLAN
Topo Id : 30
VTEP IP : 192.168.11.11
VTEP VPC IP : 0.0.0.0
Router-MAC : 0000.0000.0000
Active Export RTs : 1

Active Export RT list : 65000:10000030

Config Export RTs : 1
ExportRT cfg list:
65000:10000030 (auto)
Export RT chg/chg-pending : 0/0
Active Import RTs : 1

Active Import RT list : 65000:10000030

Config Import RTs : 1
ImportRT cfg list:
65000:10000030 (auto)
Import RT chg/chg-pending : 0/0
IMET Reg/Unreg from L2RIB : 2/0
MAC Reg/Unreg from L2RIB : 2/0
MAC IP Reg/Unreg from L2RIB : 2/0
IMET Add/Del from L2RIB : 0/0
MAC Add/Del from L2RIB : 1/0
MAC IP Add/Del from L2RIB : 1/0
IMET Dnld/Wdraw to L2RIB : 0/0
MAC Dnld/Wdraw to L2RIB : 1/0
MAC IP Dnld/Wdraw to L2RIB : 1/0

- When an update is received, irrespective of the fact of it being an Inter-VNI or Intra-VNI update, make sure that correct Route Targets (RTs) are being received and VTEP receiving the update has relevant configs. An update from VTEP3 coming via SPINE is analysed here for RT consistency. The local state of RT and RD for VTEP1 has been shown in these outputs.

<#root>

SPINE# show bgp l2vpn evpn 172.16.30.2 !

Update from Spine

BGP routing table information for VRF default, address family L2VPN EVPN
Route Distinguisher: 3.3.3.3:32797
BGP routing table entry for [2]:[0]:[0]:[48]:[8c60.4ff2.f541]:[32]:[172.16.30.2]
/272, version 25
Paths: (1 available, best #1)
Flags: (0x000202) on xmit-list, is not in l2rib/evpn, is not in HW,

Advertised path-id 1

Path type: internal, path is valid, is best path, remote nh not installed, no

labeled nexthop

AS-Path: NONE, path sourced internal to AS
192.168.33.34 (metric 5) from 192.168.33.33 (3.3.3.3)
Origin IGP, MED not set, localpref 100, weight 0
Received label 10000030 1000001

Extcommunity: RT:65000:10000010 RT:65000:10000030 SOO:192.168.33.34:0 ENC

AP:8 Router MAC:0062.ecbf.4e4d

Path-id 1 advertised to peers:

192.168.11.11 192.168.22.22 192.168.44.44