

Table 1. Cisco IOS XR 7.6.1

Table 1. Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1
Cisco IOS XR 7.6.1
Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

```
Router> show cip status
```

```
State : Enabled
```

```
Vlan : 1
```

Cisco IOS XR 7.6.1

```
Router> show cip status
```

^

```
% Invalid input detected at '^' marker.
```

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

Cisco IOS XR 7.6.1

- IOS XR 7.6.1

- NX-OS $\tilde{a}, \frac{1}{2}\tilde{a}f \cdot \tilde{a}f^{\wedge}\tilde{a}, \tilde{l}\tilde{a}, \tilde{s}\tilde{a}, \tilde{c}$

ã>žé ğç-

ã"ã®è,,†ã¼±æ€šã«ã³¼ã‡|ã™ã,ã>žé ğç-ãã,ã,šã¾ã>ã,"ã€ãÿãã—ã€ç:©ã'CE

- CIP

æ©ÿèf½ã,'ç,,jãš'ãCE-ã™ã,ã«ã"ã®è,,†ã¼±æ€šã«ã³¼ã™ã,ã»æ'fãf™ã,ãfãf«ã

æ©ÿèf½ã,'ç,,jãš'ãCE-ã™ã,ã«ã"ã€CIP

ãCEç¾ãœ"æœ%ãš'ã«ãªã£ã|ã,,ã,<VLANã®ã,ããf³ã,çãf¼ãfã,šã,ãã,¹

ã,³ãf³ãfã,£ã,®ãfãfã-fã¼ã,ãfšãf³ãfãf¼ãf%ãš no cip enable

ã,³ãfãfãfã,ã½ç"ã—ã¾ã™ã€,

- TACACS+

è"è¼ã€èãã-ã€ãšã,ã³ã,çã,ã,|ãfãftã,£ãf³ã,°i¼^AAi¼%ã,³ãfãfãfã%è"±ã-ã

ã"ã,CEã,%ã®ç:©ã'CEç-ã-ã>žã...ããã,CEã|ãšã,šã€ãftã,¹ãfç°ãçfãšã-ã®ÿè"¼æ,ã

ã:®æ£æ,ã>žã,½ãfãf^ã,|ã,šã,ç

ã,ã,¹ã,³ãã"ã"ã®ã,çãf%ãfãã,ãã,¶ãfãã«è"~è¼%ããã,CEãÿè,,†ã¼±æ€šã«ã³¼ã‡|ã™ã,ç,,j

ãfãf¼ã,ãfšãf³ãã"ãfã,£ãf¼ãfãf£

ã,»ãffãfãã«ã³¼ã—ã|ã®ãçãã"ãªã,šã¾ã™ã€,ã€ã®ã,ã"ã†ãªã,½ãfãf^ã,|ã,šã,ç

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

ã¾ãÿã€ãšã®çæšã-ãCEã,½ãfãf^ã,|ã,šã,çã,ãfã,|ãfãfãf¼ãf%ãšããã,ã®ã-ã€ã,ã

ã,çãffãf—ã,°ãfãf¼ãf%ãšã™ã€,ç,,jã,ÿã®ã,»ã,ãfãfãfãftã,£ã,½ãfãf^ã,|ã,šã,ç

ã,çãffãf—ãfãf¼ãf^ã«ã,ã£ã|ã€ãšãšã®çæšãã«æ-°ã—ã,,ã,½ãfãf^ã,|ã,šã,ç

ãf©ã,ãã,»ãf³ã,¹ã€è:½ãšã,½ãfãf^ã,|ã,šã,çãfã,£ãf¼ãfãf£

ã,»ãffãfãã¾ã¾ãÿã-ãfãã,ãf£ãf¼ãfãfãã,ãfšãf³

ã,çãffãf—ã,°ãfãf¼ãf%ãšã«ã³¼ã™ã,ã»æ"©é™ã€ãCEã»ã,žããã,CEã,ã"ã"ã-ãã,ã,šã¾ã¾ã

[ã.½ãfãf^ã.lã.šã.çã®ã,çãffãf—ã,°ãfãf¼ãf%ãšã,ãæœè"žã™ã,ã<éšãã«ã"ã€ã.ã.¹ã.³](#)

[ã.ã.ãfãfãfãftã.£ã.çãf%ãfãã,ãã,¶ãfãã](#)

[ãfšãf¼ãã,ãšã...ãœ%ããšããã,ãã,ã,¹ã,³è£½ã"ã®ã,çãf%ããfãã,ãã,¶ãfãã,ã®šæœÿçš,ã«ãç,ç](#)

ã,½ãfãfãfãf¼ãã,ãfšãf³ã,ã¼ã,çç°èãã—ã|ããããããã,ã€,

ã,,ãšã,CEã®ã'ã^ã,,ã€ãã,çãffãf—ã,°ãfãf¼ãf%ãšã™ã,ãfãfããã,ãã,¹ã«ããã^ãããfãfãã

Technical Assistance

Centeri¼^TACi¼%ã,,ã—ãããã-ã'ç',ã—ã|ã,,ã,ãfãfãfãftãfšãf³ã,¹ãf—ãfãfãã,ããfãf¼ãã

ã,ãf¼ãfã"ã,¹ã'ç',ã,ã"ã"ã^ç"ãšãªã,,ãšã®çæš~

[a½±éÿ;ã®è©•ä¾i¼^Impact Ratingi¼%o]

ã®ä,ã«ã,ã,ãf%ãfãffãf—ãf€ã,|ãf³ãfªã,¹ãf^ã® [ä,é-“i¼^Mediumi¼%o]

ãfã,šãffã,ãfœãffã,ã,¹ã,ªãf³ã«ã—ã¾ã™ã€,

Cisco IOS XE ä,½ãf•ãf^ã,lã,šã,çãfªãfªãf¼ã,¹ã Cisco IOS ä,½ãf•ãf^ã,|ã,šã,ç

ãfªãfªãf¼ã,¹ã®ãfzãffãf”ãf³ã,°ã«ã»ã,,ã|ã-ã€Cisco IOS XE

ã,½ãf•ãf^ã,|ã,šã,çã®ãfªãfªãf¼ã,¹ã«ã¿œã~ã|ã€Cisco IOS XE 2 Release

Notesã€ã€ã€Cisco IOS XE 3S Release Notesã€ã€ã¾ãÿã-ã€Cisco IOS XE 3SG

Release Notesã€ã,ã,ç...šã—ã|ããããã•ã,,ã€,

ä,æfã^©ç””ä°<ã¾ã”ã...-ã¼ç™°è;”

Cisco Product Security Incident Response

Teami¼^PSIRTi¼%oã-ã€æœ-ã,çãf%ãfã,ã,¶ã,¶ãfªã«è”~è¼%ã•ã,œã|ã,,ã,è,,†ã¼±æ€šã

ã†°ã...,

ã”ã®è,,†ã¼±æ€šã-ã€Cisco Advanced Security Initiatives Groupi¼^ASIGi¼%oã® X.B.

ã«ã,^ã,ã†...éf”ã,»ã,fªfªãfªã,£ãfªã,¹ãf^ãšç™°è|ã•ã,œã¾ã—ãÿã€,

URL

<https://tools.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-XE-SAP-OPLbze68>

æ”¹è”,ã±¥æ´

ãfãf¼ã,ãfsãf³	èª-æŽ	ã,»ã,ã,ãfšãf³	ã,¹ãfªãf¼ã,¿ã,¹	æ—¥ã~
1.0	ã^ã»ãžã...-é-ãfªãfªãf¼ã,¹	-	Final	2021 å¹´ 3 æœ^ 24 æ—¥

ã^©ç””è|ç”,,

æœ-ã,çãf%ãfã,ã,¶ã,¶ãfªã-ç,,ã¿è”¼ã®ã,,ã®ã”ã—ã|ã”æ»»ã¾ã—ã|ãšã,šã€

æœ-ã,çãf%ãfã,ã,¶ã,¶ãfªã®æf...ã±ãšã,^ã³ãfªãf³ã,ã®ã½çç””ã«é-çã™ã,«è²-ã»ã®ã,€

ã¾ãÿãÿã€ã,ã,¹ã,³ã-æœ-ãf%ã,ãfªãfªãf³ã®ã†...ã®¹ã,ª°ãšãªã—ã«ã%ãæ´ã—ã

æœ-ã,çãf%ãfã,ã,¶ã,¶ãfªã®è”~è¿ã†...ã®¹ã«é-çã—ã|æf...ã±è...ã¿ã® URL

ã,¿œçç¥ã—ã€ãçç-ã®è»çè¼%ã,,,æ,,è”³ã,æ-½ã—ãÿã´ã^ã€ã½”ç¾ãœç®çç

ã”ã®ãf%ã,ãfªãfªãf³ãf^ã®æf...ã±ã-ã€ã,ã,¹ã,³è£½ã”ã®ã,ãf³ãf%ãf|ãf¼ã,¶ã,ã¾è±ã

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。