

通过MRA对Jabber for Windows自动更新进行故障排除

目录

[简介](#)

[问题：MRA从11.7.0升级到11.8.x的升级问题](#)

[故障排除](#)

[来自非工作场景的日志分析：](#)

[工作场景：](#)

[解决方案](#)

简介

本文档介绍如何排除MRA上Jabber Windows从11.7(x)到11.8的自动更新故障。

问题：MRA从11.7.0升级到11.8.x的升级问题

您尝试通过MRA从11.7.0自动升级Jabber客户端到11.8.x。但是，即使出现更新窗口，也会失败。但是，自动升级11.6到11.8可以正常工作。

故障排除

[来自非工作场景的日志分析：](#)

- 已转换autoupdate.xml文件URL:

```
DEBUG [0x00001f14] [tutils\adapters\EdgeUtilsAdapter.cpp(39)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - About to transformRequest with
Url [http://10.106.108.146:6970/Autoupdate.xml]
```

```
DEBUG [0x00001f14] [ls\src\edge\GlobalEdgeStateImpl.cpp(780)] [csf.edge]
[csf::edge::GlobalEdgeStateImpl::checkPrecondition] - Acquired scoped lock (visibilityMutex_)
```

- 已更新转换的URL:

```
DEBUG [0x00001f14] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/Autoupdate.xml https://vcse-
mum.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/Autoupdate.xml
```

```
DEBUG [0x000014e8] [ntrol\FeatureSetEventManagerImpl.cpp(87)] [IMPServices-
PresenceAdapter.FeatureSetEventManager] [CSFUnified::FeatureSetEventManagerImpl::flushQueue] -
Adding 0 deferred events to the service dispatcher
INFO [0x0000162c] [onstabs\generaltab\src\AutoStart.cpp(34)] [AutoStart]
[AutoStart::DetermineExecutablePath] - The executable path for the client is C:\Program
Files\Cisco Systems\Cisco Jabber\CiscoJabber.exe
```

- 使用下载链接升级信息：

```
DEBUG [0x0000162c] [erupgradeplugin\UpgradesListener.cpp(80)] [JabberUpgradePlugin]
[UpgradesListener::OnUpdateChecked] - Received update information. Version number: 11.8.2 Build
number: 50390 Download link: http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule:
UpgradeAvailable: 1 UpgradeMandatory: 0
INFO [0x00000b20] [\cpve\src\main\connectionfactory.cpp(46)] [cpve]
[CSF::media::rtp::ConnectionFactoryImpl::ConnectionFactoryImpl] - Created a new
ConnectionFactory 0x099f7ef8.
```

- 升级对话框：

```
DEBUG [0x0000162c] [gradeplugin\JabberUpgradeDialog.cpp(591)] [JabberUpgradePlugin]
[JabberUpgradeDialog::OnUpdateInformationReceived] - Received update information. Version
number: 11.8.2 Build number: 50390 Download link:
http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule: UpgradeMandatory: 0
AllowUpdatesOverEdge: 0
```

```
DEBUG [0x0000162c] [gradeplugin\JabberUpgradeDialog.cpp(314)] [JabberUpgradePlugin]
[JabberUpgradeDialog::DownloadInstaller] - Temporary filename is:
C:\Users\SACHIN~1\AppData\Local\Temp\CiscoJabberSetup.msi.temp
```

- Jabber未转换msi安装程序的下载链接：

```
DEBUG [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(136)] [csf.httpclient]
[csf::http::BasicHttpClientImpl::AsyncTask::execute] - Edge policy enforced successfully with
transformed Url:http://10.106.108.146:6970/CiscoJabberSetup.msi for request #28
```

```
DEBUG [0x00001b64] [etutils\src\http\HttpRequestData.cpp(73)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Acquired lock
(_easyCurlConnectionMutex)
```

```
DEBUG [0x0000162c] [facade\IJabberToolbarEventsImpl.cpp(285)] [PluginRuntime]
[IJabberToolbarEventsImpl::onToolbarContextChanged] - Enqueuing event - CallerPluginID=105
```

```
DEBUG [0x00001b64] [etutils\src\http\HttpRequestData.cpp(82)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Releasing lock
(_easyCurlConnectionMutex)
```

- 将MSI安装程序URL直接发送到TFTP服务器，但失败。

```
信息[0x00001b64] [etutils\src\http\CurlHttpUtils.cpp(1088)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *—*配置请求#28 GET
http://10.106.108.146:6970/CiscoJabberSetup.msi
```

- Jabber客户端获取HTTP响应0以响应请求和主机无法到达错误：

```
INFO [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(452)] [csf.httpclient]
[csf::http::executeImpl] - *-----* HTTP response code 0 for request #28 to
http://10.106.108.146:6970/CiscoJabberSetup.msi
ERROR [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(457)] [csf.httpclient]
[csf::http::executeImpl] - There was an issue performing the call to curl_easy_perform for
request #28: HOST_UNREACHABLE_ERROR
```

工作场景：

- 下载Jabber设置：

DEBUG [0x0000253c] [erupgradeplugin\UpgradesListener.cpp(43)] [JabberUpgradePlugin]
[UpgradesListener::OnUpdateChecked] - Received update information. Version number: 11.8.2 Build
number: 50390 Download link: http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule:
UpgradeAvailable: 1 UpgradeMandatory: 0

DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(554)] [JabberUpgradePlugin]
[JabberUpgradeDialog::OnUpdateInformationReceived] - Received update information. Version
number: 11.8.2 Build number: 50390 Download link:
http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule: UpgradeMandatory: 0
INFO [0x0000253c] [win\src\ceb\src\trident\trident.cpp(218)] [ceb.trident]
[trident::CTrident::stopNavigation] - Attempting to call stop on the browser - checking if the
browser is navigating

DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(275)] [JabberUpgradePlugin]
[JabberUpgradeDialog::DownloadInstaller] - Starting download
2017-03-27 15:53:31,554 DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(289)]
[JabberUpgradePlugin] [JabberUpgradeDialog::DownloadInstaller] - Temporary filename is:
C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(39)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - About to transformRequest with
Url [http://10.106.108.146:6970/CiscoJabberSetup.msi]
2017-03-27 15:53:31,555 DEBUG [0x00002540] [ls\src\edge\GlobalEdgeStateImpl.cpp(774)] [csf.edge]
[csf::edge::GlobalEdgeStateImpl::checkPrecondition] - Acquired scoped lock (visibilityMutex_

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
https://vcse-hyd.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
https://vcse-hyd.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

DEBUG [0x00002540] [\common\ScopedWinSockInitialiser.cpp(50)] [csf.netutils.common]
[csf::ip::ScopedWinSockInitialiser::ScopedWinSockInitialiser] - Winsock.dll details -
Description: WinSock 2.0, System Status: Running.

DEBUG [0x00002540] [ls\src\http\BasicHttpClientImpl.cpp(132)] [csf.httpclient]
[csf::http::BasicHttpClientImpl::AsyncTask::execute] - Edge policy enforced successfully with
transformed Url:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi for
request #101

DEBUG [0x00002540] [etutils\src\http\HttpRequestData.cpp(73)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Acquired lock
(_easyCurlConnectionMutex)

DEBUG [0x00002540] [etutils\src\http\HttpRequestData.cpp(82)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Releasing lock
(_easyCurlConnectionMutex)

INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1087)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *-----* Configuring request #101 GET
https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1732)] [csf.httpclient]
[csf::http::CurlHeaders::CurlHeaders] - Number of Request Headers : 1
2017-03-27 15:53:31,556 DEBUG [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1143)]
[csf.httpclient] [csf::http::CurlHttpUtils::configureEasyRequest] - Successfully test-opened
file with write option C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp

```
DEBUG [0x00002540] [tutils\src\http\HttpRequestData.cpp(111)] [csf.httpclient]
[csf::http::HttpRequestData::switchToNextUrl] - switching to next url: https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
```

- 正在发送MSI安装程序请求。

```
INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1087)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *-----* Configuring request #101 GET
https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
```

```
INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1732)] [csf.httpclient]
[csf::http::CurlHeaders::CurlHeaders] - Number of Request Headers : 1
DEBUG [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1143)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - Successfully test-opened file with write
option C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp
DEBUG [0x00002540] [netutils\src\http\CurlHttpUtils.cpp(986)] [csf.httpclient]
[csf::http::CurlHttpUtils::closeFile] - Closing file
```

解决方案

此参数应从Jabber版本11.7显式添加到Jabber更新参数下的Jabber更新文件中，以便通过MRA成功自动升级。在Jabber版本11.6之前，它默认启用：

```
<AllowUpdatesViaExpressway>true</AllowUpdatesViaExpressway>
```

本文档的缺陷也在此处打开：

<http://cdets.cisco.com/apps/dumpcr?content=summary&format=html&identifier=CSCvd85090>