

對通過MRA的Windows自動更新的Jabber進行故障排除

目錄

[簡介](#)

[問題：MRA從11.7.0升級到11.8.x的問題](#)

[疑難排解](#)

[非工作方案中的日誌分析：](#)

[工作場景：](#)

[解決方案](#)

簡介

本文描述如何對11.7(x)到11.8的Jabber Windows over MRA的自動更新故障進行故障排除。

問題：MRA從11.7.0升級到11.8.x的問題

您嘗試通過MRA自動將Jabber客戶端從11.7.0升級到11.8.x。但是，即使出現更新視窗，它也會失敗。而11.6到11.8的自動升級工作正常。

疑難排解

非工作方案中的日誌分析：

- 已轉換autoupdate.xml檔案URL:

```
DEBUG [0x00001f14] [tutils\adapters\EdgeUtilsAdapter.cpp(39)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - About to transformRequest with
Url [http://10.106.108.146:6970/Autoupdate.xml]
```

```
DEBUG [0x00001f14] [ls\src\edge\GlobalEdgeStateImpl.cpp(780)] [csf.edge]
[csf::edge::GlobalEdgeStateImpl::checkPrecondition] - Acquired scoped lock (visibilityMutex_)
```

- 已更新的轉換URL:

```
DEBUG [0x00001f14] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/Autoupdate.xml https://vcse-
mum.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/Autoupdate.xml
```

```
DEBUG [0x000014e8] [ntrol\FeatureSetEventManagerImpl.cpp(87)] [IMPServices-
PresenceAdapter.FeatureSetEventManager] [CSFUnified::FeatureSetEventManagerImpl::flushQueue] -
Adding 0 deferred events to the service dispatcher
INFO [0x0000162c] [onstabs\generaltab\src\AutoStart.cpp(34)] [AutoStart]
[AutoStart::DetermineExecutablePath] - The executable path for the client is C:\Program
Files\Cisco Systems\Cisco Jabber\CiscoJabber.exe
```

- 使用下載連結升級資訊：

```
DEBUG [0x0000162c] [erupgradeplugin\UpgradesListener.cpp(80)] [JabberUpgradePlugin]
[UpgradesListener::OnUpdateChecked] - Received update information. Version number: 11.8.2 Build
number: 50390 Download link: http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule:
UpgradeAvailable: 1 UpgradeMandatory: 0
INFO [0x00000b20] [\cpve\src\main\connectionfactory.cpp(46)] [cpve]
[CSF::media::rtp::ConnectionFactoryImpl::ConnectionFactoryImpl] - Created a new
ConnectionFactory 0x099f7ef8.
```

- 升級對話方塊：

```
DEBUG [0x0000162c] [gradeplugin\JabberUpgradeDialog.cpp(591)] [JabberUpgradePlugin]
[JabberUpgradeDialog::OnUpdateInformationReceived] - Received update information. Version
number: 11.8.2 Build number: 50390 Download link:
http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule: UpgradeMandatory: 0
AllowUpdatesOverEdge: 0
```

```
DEBUG [0x0000162c] [gradeplugin\JabberUpgradeDialog.cpp(314)] [JabberUpgradePlugin]
[JabberUpgradeDialog::DownloadInstaller] - Temporary filename is:
C:\Users\SACHIN~1\AppData\Local\Temp\CiscoJabberSetup.msi.temp
```

- Jabber未轉換msi安裝程式的下載連結：

```
DEBUG [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(136)] [csf.httpclient]
[csf::http::BasicHttpClientImpl::AsyncTask::execute] - Edge policy enforced successfully with
transformed Url:http://10.106.108.146:6970/CiscoJabberSetup.msi for request #28
```

```
DEBUG [0x00001b64] [etutils\src\http\HttpRequestData.cpp(73)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Acquired lock
(_easyCurlConnectionMutex)
```

```
DEBUG [0x0000162c] [facade\IJabberToolbarEventsImpl.cpp(285)] [PluginRuntime]
[IJabberToolbarEventsImpl::onToolbarContextChanged] - Enqueuing event - CallerPluginID=105
```

```
DEBUG [0x00001b64] [etutils\src\http\HttpRequestData.cpp(82)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Releasing lock
(_easyCurlConnectionMutex)
```

- 將MSI安裝程式URL直接傳送到TFTP伺服器失敗。

```
資訊[0x00001b64] [etutils\src\http\CurlHttpUtils.cpp(1088)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *----*配置請求#28獲取
http://10.106.108.146:6970/CiscoJabberSetup.msi
```

- Jabber使用者端會收到要求的HTTP回應0和主機無法連線錯誤：

```
INFO [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(452)] [csf.httpclient]
[csf::http::executeImpl] - *-----* HTTP response code 0 for request #28 to
http://10.106.108.146:6970/CiscoJabberSetup.msi
ERROR [0x00001b64] [ls\src\http\BasicHttpClientImpl.cpp(457)] [csf.httpclient]
[csf::http::executeImpl] - There was an issue performing the call to curl_easy_perform for
request #28: HOST_UNREACHABLE_ERROR
```

工作場景：

- 正在下載Jabber設定：

DEBUG [0x0000253c] [erupgradeplugin\UpgradesListener.cpp(43)] [JabberUpgradePlugin]
[UpgradesListener::OnUpdateChecked] - Received update information. Version number: 11.8.2 Build
number: 50390 Download link: http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule:
UpgradeAvailable: 1 UpgradeMandatory: 0

DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(554)] [JabberUpgradePlugin]
[JabberUpgradeDialog::OnUpdateInformationReceived] - Received update information. Version
number: 11.8.2 Build number: 50390 Download link:
http://10.106.108.146:6970/CiscoJabberSetup.msi Upgrade rule: UpgradeMandatory: 0
INFO [0x0000253c] [win\src\ceb\src\trident\trident.cpp(218)] [ceb.trident]
[trident::CTrident::stopNavigation] - Attempting to call stop on the browser - checking if the
browser is navigating

DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(275)] [JabberUpgradePlugin]
[JabberUpgradeDialog::DownloadInstaller] - Starting download
2017-03-27 15:53:31,554 DEBUG [0x0000253c] [gradeplugin\JabberUpgradeDialog.cpp(289)]
[JabberUpgradePlugin] [JabberUpgradeDialog::DownloadInstaller] - Temporary filename is:
C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(39)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - About to transformRequest with
Url [http://10.106.108.146:6970/CiscoJabberSetup.msi]
2017-03-27 15:53:31,555 DEBUG [0x00002540] [ls\src\edge\GlobalEdgeStateImpl.cpp(774)] [csf.edge]
[csf::edge::GlobalEdgeStateImpl::checkPrecondition] - Acquired scoped lock (visibilityMutex_

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
https://vcse-hyd.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

DEBUG [0x00002540] [tutils\adapters\EdgeUtilsAdapter.cpp(63)] [csf.netutils.adapters]
[csf::netutils::adapters::EdgeUtilsAdapter::transformRequest] - Transformed Urls:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
https://vcse-hyd.hpcl.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

DEBUG [0x00002540] [\common\ScopedWinSockInitialiser.cpp(50)] [csf.netutils.common]
[csf::ip::ScopedWinSockInitialiser::ScopedWinSockInitialiser] - Winsock.dll details -
Description: WinSock 2.0, System Status: Running.

DEBUG [0x00002540] [ls\src\http\BasicHttpClientImpl.cpp(132)] [csf.httpclient]
[csf::http::BasicHttpClientImpl::AsyncTask::execute] - Edge policy enforced successfully with
transformed Url:https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi for
request #101

DEBUG [0x00002540] [etutils\src\http\HttpRequestData.cpp(73)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Acquired lock
(_easyCurlConnectionMutex)

DEBUG [0x00002540] [etutils\src\http\HttpRequestData.cpp(82)] [csf.httpclient]
[csf::http::HttpRequestData::consumeEasyCURLConnection] - Releasing lock
(_easyCurlConnectionMutex)

INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1087)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *-----* Configuring request #101 GET
https://vcse-
test1.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi

INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1732)] [csf.httpclient]
[csf::http::CurlHeaders::CurlHeaders] - Number of Request Headers : 1
2017-03-27 15:53:31,556 DEBUG [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1143)]
[csf.httpclient] [csf::http::CurlHttpUtils::configureEasyRequest] - Successfully test-opened
file with write option C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp

```
DEBUG [0x00002540] [tutils\src\http\HttpRequestData.cpp(111)] [csf.httpclient]
[csf::http::HttpRequestData::switchToNextUrl] - switching to next url: https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
```

- 正在傳送MSI安裝程式請求。

```
INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1087)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - *-----* Configuring request #101 GET
https://vcse-
test.ucis.co.in:8443/aHBjbC5jby5pbi9odHRwLzEwLjE1LjAuMzMvNjk3MA/CiscoJabberSetup.msi
```

```
INFO [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1732)] [csf.httpclient]
[csf::http::CurlHeaders::CurlHeaders] - Number of Request Headers : 1
DEBUG [0x00002540] [etutils\src\http\CurlHttpUtils.cpp(1143)] [csf.httpclient]
[csf::http::CurlHttpUtils::configureEasyRequest] - Successfully test-opened file with write
option C:\Users\Abhishek\AppData\Local\Temp\CiscoJabberSetup.msi.temp
DEBUG [0x00002540] [netutils\src\http\CurlHttpUtils.cpp(986)] [csf.httpclient]
[csf::http::CurlHttpUtils::closeFile] - Closing file
```

解決方案

為了通過MRA成功進行自動升級，應從Jabber 11.7版顯式地將此引數新增到Jabber更新檔案的Jabber更新引數下。在Jabber 11.6版之前，預設情況下會啟用：

```
<AllowUpdatesViaExpressway>true</AllowUpdatesViaExpressway>
```

此文檔缺陷也在此處開啟：

<http://cdets.cisco.com/apps/dumpcr?content=summary&format=html&identifier=CSCvd85090>